

Light Commercial Commercial Comfort



Commercial comfort. No compromise.

Get curb appeal, energy efficient performance and outstanding product limited warranties*.

Get on the ground floor with one of the world's largest HVAC manufacturers and start growing your business. Daikin commercial splits and packaged units offer ease of installation, efficient operation and outstanding product limited warranty* coverage. Whether you need a straight cooling unit, heat pump or gas/electric, you'll find cogent features such as 5mm condensing coils, outstanding heat pump features and our most durable tubular heat exchanger. When you want the best, don't compromise. Demand Daikin!

*Complete warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

Light Commercial Product Overview

Light Commercial Split	Air Conditioner	Standard Efficiency		DX14 series 3-5 ton
				DX14 series 7½ and 10 ton
	Heat Pump	Standard Efficiency		DZ14 series 3-5 ton
				DZ14 series 7½ and 10 ton
	Air Handler	Standard Efficiency		DAX series Multi-position
Light Commercial Packaged	Gas/Electric	High Efficiency		DRG series 3-6 ton
				DRG series 7½-12½ ton
		Standard Efficiency		DFG series 3-6 ton
				DFG series 7½-12½ ton
	Air Conditioner	High Efficiency		DRC series 3-6 ton
				DRC series 7½-12½ ton
		Standard Efficiency		DFC series 3-6 ton
				DFC series 7½-12½ ton
				DFC series 15-25 ton
	Heat Pump	High Efficiency		DRH series 3-6 ton
		Standard Efficiency		DFH series 3-5 ton
				DFH series 7½-10 ton

DFC – Standard-Efficiency Air Conditioner Direct-Drive 3 to 5 Tons



*Complete warranty details available from your local dealer/contractor or manufacturer's representative or at www.daikincomfort.com.

The Daikin DFC Commercial Packaged Air Conditioners feature high-efficiency scroll compressors, and easy access for servicing. These units are housed in a heavy-gauge, galvanized-steel cabinet with UV-resistant powder-paint finish.



DESIGNED FOR EXCEPTIONAL DURABILITY, ENERGY EFFICIENCY, AND OUTSTANDING PERFORMANCE.

- | | | |
|--|--|--|
| <ul style="list-style-type: none"> » R-410A chlorine-free refrigerant » Direct-Drive supply fan » Copper tube/aluminum fin coils and Micro Channel condensers | <ul style="list-style-type: none"> » 24-volt Electromechanical controls package » Easy accessibility using our tool-less filter access » Screw on style pressure switches for ease of replacement | <ul style="list-style-type: none"> » Convertible airflow orientation to serve downflow or horizontal applications » AHRI Certified; ETL Listed » Built to be a direct replacement for most rooftop units without the need of a curb adapter |
|--|--|--|

Model	Nominal Capacities ¹		EER2/SEER2	Voltage-Phase	Electric Heat (kW)	Dimensions			Sound Level dB(A)	Ship Weight (lbs)
	Cooling	CFM				W"	D"	H"		
DFC0361D000001S	35,000	1,160	11/13.4	208/230-1	5,10,15	73 $\frac{3}{8}$	47 $\frac{5}{8}$	39 $\frac{7}{8}$	73	554
DFC0363D000001S	35,000	1,160	11/13.4	208/230-3	5,10,15	73 $\frac{3}{8}$	47 $\frac{5}{8}$	39 $\frac{7}{8}$	73	552
DFC0364D000001S	35,000	1,160	11/13.4	460-3	5,10,15	73 $\frac{3}{8}$	47 $\frac{5}{8}$	39 $\frac{7}{8}$	73	560
DFC0367D000001S	35,000	1,160	11/13.4	575-3	5,10,15	73 $\frac{3}{8}$	47 $\frac{5}{8}$	39 $\frac{7}{8}$	73	560
DFC0481D000001S	47,000	1,570	11/13.4	208/230-1	5,10,15,20	73 $\frac{3}{8}$	48 $\frac{5}{16}$	39 $\frac{7}{8}$	78.4	577
DFC0483D000001S	47,000	1,570	11/13.4	208/230-3	5,10,15,20	73 $\frac{3}{8}$	48 $\frac{5}{16}$	39 $\frac{7}{8}$	78.4	572
DFC0484D000001S	47,000	1,570	11/13.4	460-3	5,10,15,20	73 $\frac{3}{8}$	47 $\frac{5}{8}$	39 $\frac{7}{8}$	78.4	576
DFC0487D000001S	47,000	1,570	11/13.4	575-3	5,10,15,20	73 $\frac{3}{8}$	47 $\frac{5}{8}$	39 $\frac{7}{8}$	78.4	576
DFC0601D000001S	59,000	1,820	11/13.4	208/230-1	5,10,15,20	74	48 $\frac{5}{16}$	39 $\frac{7}{8}$	78.3	582
DFC0603D000001S	59,000	1,820	11/13.4	208/230-3	5,10,15,20	74	48 $\frac{5}{16}$	39 $\frac{7}{8}$	78.3	578
DFC0604D000001S	59,000	1,820	11/13.4	460-3	5,10,15,20	74	48 $\frac{5}{16}$	39 $\frac{7}{8}$	78.3	582
DFC0607D000001S	59,000	1,820	11/13.4	575-3	5,10,15,20	74	48 $\frac{5}{16}$	39 $\frac{7}{8}$	78.3	582

¹ BTU/h | Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.



*Complete warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

DFC – Standard-Efficiency Air Conditioner Direct-Drive 6Tons



The Daikin DFC Commercial Packaged Air Conditioners feature high-efficiency scroll compressors, two-stage cooling, and easy access for servicing. These units are housed in a heavy-gauge, galvanized-steel cabinet with UV-resistant powder-paint finish.

DESIGNED FOR EXCEPTIONAL DURABILITY, ENERGY EFFICIENCY, AND OUTSTANDING PERFORMANCE.

- » R-410A chlorine-free refrigerant
- » Two-stage scroll compressor for partial load applications
- » Direct-Drive supply fan
- » Screw on style pressure switches for ease of replacement
- » Copper tube/aluminum fin coils and Micro Channel condensers
- » 24-volt Electromechanical controls package
- » Easy accessibility using our tool-less filter access
- » Convertible airflow orientation to serve downflow or horizontal applications
- » AHRI Certified; ETL Listed
- » Built to be a direct replacement for most rooftop units without the need of a curb adapter

Model	Nominal Capacities ¹		EER / IEER	Voltage-Phase	Electric Heat (kW)	Dimensions			Sound Level dB(A)	Ship Weight (lbs)
	Cooling	CFM				W"	D"	H"		
DFC0723D000001S	69,000	2,100	11.2/15.5	208/230-3	5,10,15,20,30	74	48 5/16	43 1/2	81	724
DFC0724D000001S	69,000	2,100	11.2/15.5	460-3	5,10,15,20,30	74	48 5/16	43 1/2	81	724
DFC0727D000001S	69,000	2,100	11.2/15.5	575-3	5,10,15,20,30	74	48 5/16	43 1/2	81	724
DFC0723W000001F	69,000	2,100	11.2/15.5	208/230-3	5,10,15,20,30	74	48 5/16	43 1/2	81	724
DFC0724W000001F	69,000	2,100	11.2/15.5	460-3	5,10,15,20,30	74	48 5/16	43 1/2	81	724
DFC0727W000001F	69,000	2,100	11.2/15.5	575-3	5,10,15,20,30	74	48 5/16	43 1/2	81	724

¹ BTU/h | Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.

DFC – Standard-Efficiency Air Conditioner Direct-Drive 7½ to 12½ Tons



*Complete warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

The Daikin DFC Commercial Packaged Air Conditioners feature high-efficiency scroll compressors, two-stage cooling, and easy access for servicing. These units are housed in a heavy-gauge, galvanized-steel cabinet with UV-resistant powder-paint finish.



DESIGNED FOR EXCEPTIONAL DURABILITY, ENERGY EFFICIENCY, AND OUTSTANDING PERFORMANCE.

- » R-410A chlorine-free refrigerant
- » Two (2) single-stage scroll compressors individually circuited
- » Direct-Drive supply fan
- » Screw on style pressure switches for ease of replacement
- » Copper tube/aluminum fin coils and Micro Channel condensers
- » 24-volt Electromechanical controls package
- » Easy accessibility using our tool-less filter access
- » Convertible airflow orientation to serve downflow or horizontal applications
- » AHRI Certified; ETL Listed
- » Built to be a direct replacement for most rooftop units without the need of a curb adapter

Model	Nominal Capacities ¹		EER / IEER	Voltage-Phase	Electric Heat (kW)	Dimensions			Sound Level dB(A)	Ship Weight (lbs)
	Cooling	CFM				W"	D"	H"		
DFC0903D000001S	86,000	3,020	11.2/15	208/230-3	15,30,45	90⅝	60⅜ ₁₆	54⅝	82.6	1060
DFC0904D000001S	86,000	3,020	11.2/15	460-3	15,30,45	90⅝	60⅜ ₁₆	54⅝	82.6	1060
DFC0907D000001S	86,000	3,020	11.2/15	575-3	15,30,45	90⅝	60⅜ ₁₆	54⅝	82.6	1060
DFC1023D000001S	97,000	3,230	11.2/15	208/230-3	15,30,45	90⅝	60⅜ ₁₆	54⅝	82.6	1080
DFC1024D000001S	97,000	3,230	11.2/15	460-3	15,30,45	90⅝	60⅜ ₁₆	54⅝	82.6	1080
DFC1027D000001S	97,000	3,230	11.2/15	575-3	15,30,45	90⅝	60⅜ ₁₆	54⅝	82.6	1080
DFC1203D000001S	116,000	3,380	11.2/15	208/230-3	15,30,45	90⅝	60⅜ ₁₆	54⅝	82.6	1139
DFC1204D000001S	116,000	3,380	11.2/15	460-3	15,30,45	90⅝	60⅜ ₁₆	54⅝	82.6	1139
DFC1207D000001S	116,000	3,380	11.2/15	575-3	15,30,45	90⅝	60⅜ ₁₆	54⅝	82.6	1139
DFC1503D000001S	140,000	4,200	11/14.4	208/230-3	15,30,45	90⅝	60⅜ ₁₆	54⅝	86.8	1230
DFC1504D000001S	140,000	4,200	11/14.4	460-3	15,30,45	90⅝	60⅜ ₁₆	54⅝	86.8	1230
DFC1507D000001S	140,000	4,200	11/14.4	575-3	15,30,45	90⅝	60⅜ ₁₆	54⅝	86.8	1230
DFC1503L000001F	140,000	4,200	11/14.4	208/230-3	15,30,45	90⅝	60⅜ ₁₆	54⅝	86.8	1230
DFC1504L000001F	140,000	4,200	11/14.4	460-3	15,30,45	90⅝	60⅜ ₁₆	54⅝	86.8	1230
DFC1507L000001F	140,000	4,200	11/14.4	575-3	15,30,45	90⅝	60⅜ ₁₆	54⅝	86.8	1230

¹ BTU/h | Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.



*Complete warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

DFC – Standard-Efficiency Air Conditioner Direct-Drive 15 to 25 Tons



The Daikin DFC Commercial Packaged Air Conditioners feature high-efficiency scroll compressors, two-stage cooling, and easy access for servicing. These units are housed in a heavy-gauge, galvanized-steel cabinet with UV-resistant powder-paint finish.

DESIGNED FOR EXCEPTIONAL DURABILITY, ENERGY EFFICIENCY, AND OUTSTANDING PERFORMANCE.

- » R-410A chlorine-free refrigerant
- » Two (2) single-stage scroll compressors individually circuited
- » Two (2) direct-drive supply fans
- » 24-volt Electromechanical controls package
- » Screw on style pressure switches for ease of replacement
- » Copper tube/aluminum fin coils and Micro Channel condensers
- » Dedicated downflow orientation convertible with an adapter.
- » AHRI Certified; ETL Listed
- » Screw on style pressure switches for ease of replacement

Model	Nominal Capacities ¹		EER / IEER	Voltage-Phase	Electric Heat (kW)	Dimensions			Sound Level dB(A)	Ship Weight (lbs)
	Cooling	CFM				W"	D"	H"		
DFC1803D000001S	172,000	5,000	11/14	208/230-3	30,45,60	133 ⁷ / ₈	88 ¹ / ₂	51 ¹ / ₃	88	1839
DFC1804D000001S	172,000	5,000	11/14	460-3	30,45,60	133 ⁷ / ₈	88 ¹ / ₂	51 ¹ / ₃	88	1839
DFC1807D000001S	172,000	5,000	11/14	575-3	30,45,60	133 ⁷ / ₈	88 ¹ / ₂	51 ¹ / ₃	88	1839
DFC2403D000001S	230,000	6,500	11/14	208/230-3	30,45,60,75	133 ⁷ / ₈	88 ¹ / ₂	51	88	2108
DFC2404D000001S	230,000	6,500	11/14	460-3	30,45,60,75	133 ⁷ / ₈	88 ¹ / ₂	51	88	2108
DFC2407D000001S	230,000	6,500	11/14	575-3	30,45,60,75	133 ⁷ / ₈	88 ¹ / ₂	51	88	2108
DFC3003D000001S	290,000	8,200	10/13	208/230-3	30,45,60,75	133 ⁷ / ₈	88 ¹ / ₂	51	92	2198
DFC3004D000001S	290,000	8,200	10/13	460-3	30,45,60,75	133 ⁷ / ₈	88 ¹ / ₂	51	92	2198
DFC3007D000001S	290,000	8,200	10/13	575-3	30,45,60,75	133 ⁷ / ₈	88 ¹ / ₂	51	92	2198

¹ BTU/h | Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.

DRC – High-Efficiency Air Conditioner Direct-Drive 3 to 5 Tons



*Complete warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

The Daikin DRC Commercial Packaged Air Conditioners feature high-efficiency scroll compressors, two-stage cooling, and easy access for servicing. These units are housed in a heavy-gauge, galvanized-steel cabinet with UV-resistant powder-paint finish.



DESIGNED FOR EXCEPTIONAL DURABILITY, ENERGY EFFICIENCY, AND OUTSTANDING PERFORMANCE.

- » R-410A chlorine-free refrigerant
- » Two-stage scroll compressor
- » ECM Direct-Drive supply fan
- » Copper tube/aluminum fin coils on condenser and evaporator
- » 24-volt Electromechanical controls package
- » Easy accessibility using our tool-less filter access
- » Convertible airflow orientation to serve downflow or horizontal applications
- » AHRI Certified; ETL Listed
- » Built to be a direct replacement for most rooftop units without the need of a curb adapter

Model	Nominal Capacities ¹		SEER2/EER2	Voltage-Phase	Electric Heat (kW)	Dimensions			Sound Level dB(A)	Ship Weight (lbs)
	Cooling	CFM				W"	D"	H"		
DRC0361D000001S	36,000	1,180	16.4/12.1	208/230-1	5,10,15	74	47 $\frac{1}{2}$	39 $\frac{1}{2}$	75	595
DRC0363D000001S	36,000	1,180	16.4/12.1	208/230-3	5,10,15	74	47 $\frac{1}{2}$	39 $\frac{1}{2}$	75	595
DRC0364D000001S	36,000	1,180	16.4/12.1	460-3	5,10,15	74	47 $\frac{1}{2}$	39 $\frac{1}{2}$	75	595
DRC0367D000001S	36,000	1,180	16.4/12.1	575-3	5,10,15	74	47 $\frac{1}{2}$	39 $\frac{1}{2}$	75	595
DRC0481D000001S	47,000	1,500	16.4/12	208/230-1	5,10,15,20	74	47 $\frac{1}{2}$	43 $\frac{1}{2}$	73	648
DRC0483D000001S	47,000	1,500	16.4/12	208/230-3	5,10,15,20	74	47 $\frac{1}{2}$	43 $\frac{1}{2}$	73	648
DRC0484D000001S	47,000	1,500	16.4/12	460-3	5,10,15,20	74	47 $\frac{1}{2}$	43 $\frac{1}{2}$	73	648
DRC0487D000001S	47,000	1,500	16.4/12	575-3	5,10,15,20	74	47 $\frac{1}{2}$	43 $\frac{1}{2}$	73	648
DRC0601D000001S	58,000	1,850	16.2/11.9	208/230-1	5,10,15,20	74	47 $\frac{1}{2}$	43 $\frac{1}{2}$	76	664
DRC0603D000001S	58,000	1,850	16.2/11.9	208/230-3	5,10,15,20	74	47 $\frac{1}{2}$	43 $\frac{1}{2}$	76	664
DRC0604D000001S	58,000	1,850	16.2/11.9	460-3	5,10,15,20	74	47 $\frac{1}{2}$	43 $\frac{1}{2}$	76	664
DRC0607D000001S	58,000	1,850	16.2/11.9	575-3	5,10,15,20	74	47 $\frac{1}{2}$	43 $\frac{1}{2}$	76	664

¹ BTU/h | Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.



*Complete warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

DRC – High-Efficiency Air Conditioner Direct-Drive 6 Tons



The Daikin DRC Commercial Packaged Air Conditioners feature high-efficiency scroll compressors, two-stage cooling, and easy access for servicing. These units are housed in a heavy-gauge, galvanized-steel cabinet with UV-resistant powder-paint finish.

DESIGNED FOR EXCEPTIONAL DURABILITY, ENERGY EFFICIENCY, AND OUTSTANDING PERFORMANCE.

- » R-410A chlorine-free refrigerant
- » Two-stage scroll compressor
- » ECM Direct-Drive supply fan
- » Copper tube/aluminum fin coils on condenser and evaporator
- » 24-volt Electromechanical controls package
- » Easy accessibility using our tool-less filter access
- » Convertible airflow orientation to serve downflow or horizontal applications
- » AHRI Certified; ETL Listed
- » Built to be a direct replacement for most rooftop units without the need of a curb adapter

Model	Nominal Capacities ¹		IEER / EER	Voltage-Phase	Electric Heat (kW)	Dimensions			Sound Level dB(A)	Ship Weight (lbs)
	Cooling	CFM				W"	D"	H"		
DRC0723D000001S	72,000	2,200	17.1/12.1	208/230-3	5,10,15,20,30	74	47 ⁵ / ₈	53 ³ / ₄	81	715
DRC0724D000001S	72,000	2,200	17.1/12.2	460-3	5,10,15,20,30	74	47 ⁵ / ₈	53 ³ / ₄	81	715
DRC0727D000001S	72,000	2,200	17.1/12.3	575-3	5,10,15,20,30	74	47 ⁵ / ₈	53 ³ / ₄	81	715

¹ BTU/h | Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.

DRC – High-Efficiency Air Conditioner Direct-Drive 7½ to 12½ Tons



*Complete warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

The Daikin DRC Commercial Packaged Air Conditioners feature high-efficiency scroll compressors, two-stage cooling, and easy access for servicing. These units are housed in a heavy-gauge, galvanized-steel cabinet with UV-resistant powder-paint finish.



DESIGNED FOR EXCEPTIONAL DURABILITY, ENERGY EFFICIENCY, AND OUTSTANDING PERFORMANCE.

- » R-410A chlorine-free refrigerant
- » Two-stage scroll compressor
- » ECM Direct-Drive supply fan
- » Copper tube/aluminum fin coils on condenser and evaporator
- » 24-volt Electromechanical controls package
- » Easy accessibility using our tool-less filter access
- » Convertible airflow orientation to serve downflow or horizontal applications
- » AHRI Certified; ETL Listed
- » Built to be a direct replacement for most rooftop units without the need of a curb adapter

Model	Nominal Capacities ¹		EER / IEER	Voltage-Phase	Electric Heat (kW)	Dimensions			Sound Level dB(A)	Ship Weight (lbs)
	Cooling	CFM				W"	D"	H"		
DRC0903D000001S	90,000	3,000	12.4/17	208/230-3	10,15,20,30,45	93¾	60¾	54¾ ₂₀	83	1162
DRC0904D000001S	90,000	3,000	12.4/17	460-3	10,15,20,30,45	93¾	60¾	54¾ ₂₀	83	1162
DRC0907D000001S	90,000	3,000	12.4/17	575-3	10,15,20,30,45	93¾	60¾	54¾ ₂₀	83	1162
DRC1023D000001S	102,000	3,100	12.3/17	208/230-3	10,15,20,30,45	93¾	60¾	54¾ ₂₀	80	1173
DRC1024D000001S	102,000	3,100	12.3/17	460-3	10,15,20,30,45	93¾	60¾	54¾ ₂₀	80	1173
DRC1027D000001S	102,000	3,100	12.3/17	575-3	10,15,20,30,45	93¾	60¾	54¾ ₂₀	80	1173
DRC1203D000001S	115,000	3,550	12.2/17	208/230-3	10,15,20,30,45,60	93¾	60¾	54¾ ₂₀	82	1192
DRC1204D000001S	115,000	3,550	12.2/17	460-3	10,15,20,30,45,60	93¾	60¾	54¾ ₂₀	82	1192
DRC1207D000001S	115,000	3,550	12.2/17	575-3	10,15,20,30,45,60	93¾	60¾	54¾ ₂₀	82	1192
DRC1503D000001S	137,000	3,800	11.7/16	208/230-3	10,15,20,30,45,60	93¾	60¾	58¾	81	1270
DRC1504D000001S	137,000	3,800	11.7/16	460-3	10,15,20,30,45,60	93¾	60¾	58¾	81	1270
DRC1507D000001S	137,000	3,800	11.7/16	575-3	10,15,20,30,45,60	93¾	60¾	58¾	81	1270

¹ BTU/h | Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.



*Complete warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

DFH – Standard-Efficiency Heat Pump Direct-Drive 3 to 5 Tons



The Daikin DFH Commercial Packaged Heat Pumps feature high-efficiency scroll compressors, two-stage cooling, and easy access for servicing. These units are housed in a heavy-gauge, galvanized-steel cabinet with UV-resistant powder-paint finish.

DESIGNED FOR EXCEPTIONAL DURABILITY, ENERGY EFFICIENCY, AND OUTSTANDING PERFORMANCE.

- » R-410A chlorine-free refrigerant
- » Direct-Drive supply fan
- » Copper tube/aluminum fin coils and Micro Channel condensers
- » Screw on style pressure switches for ease of replacement
- » 24-volt Electromechanical controls package
- » Easy accessibility using our tool-less filter access
- » Convertible airflow orientation to serve downflow or horizontal applications
- » AHRI Certified; ETL Listed
- » Built to be a direct replacement for most rooftop units without the need of a curb adapter

Model	Nominal Capacities ¹			EER2	SEER2	HSPF2	Voltage-Phase	Electric Heat (kW)	Dimensions			Sound Level dB(A)	Ship Weight (lbs)
	Cooling	CFM	Heating						W"	D"	H"		
DFH0361D000001S	35,000	1,170	33,400	11	13.4	6.7	208/230-1	5,10,15	74	48 ⁵ / ₁₆	39 ⁷ / ₈	73	606
DFH0363D000001S	35,000	1,170	33,400	11	13.4	6.7	208/230-3	5,10,15	74	48 ⁵ / ₁₆	39 ⁷ / ₈	73	605
DFH0364D000001S	35,000	1,170	33,400	11	13.4	6.7	460-3	5,10,15	74	48 ⁵ / ₁₆	39 ⁷ / ₈	73	613
DFH0367D000001S	35,000	1,170	33,400	11	13.4	6.7	575-3	5,10,15	74	48 ⁵ / ₁₆	39 ⁷ / ₈	73	613
DFH0481D000001S	46,000	1,600	46,000	11	13.4	6.7	208/230-1	5,10,15,20	74	48 ⁵ / ₁₆	39 ⁷ / ₈	78.4	657
DFH0483D000001S	46,000	1,600	46,000	11	13.4	6.7	208/230-3	5,10,15,20	74	48 ⁵ / ₁₆	39 ⁷ / ₈	78.4	652
DFH0484D000001S	46,000	1,600	46,000	11	13.4	6.7	460-3	5,10,15,20	74	48 ⁵ / ₁₆	39 ⁷ / ₈	78.4	656
DFH0487D000001S	46,000	1,600	46,000	11	13.4	6.7	575-3	5,10,15,20	74	48 ⁵ / ₁₆	39 ⁷ / ₈	78.4	656
DFH0601D000001S	58,000	1,840	54,000	11	13.4	6.7	208/230-1	5,10,15,20	74	48 ⁵ / ₁₆	43 ¹ / ₂	78.3	670
DFH0603D000001S	58,000	1,840	54,000	11	13.4	6.7	208/230-3	5,10,15,20	74	48 ⁵ / ₁₆	39 ⁷ / ₈	78.3	666
DFH0604D000001S	58,000	1,840	54,000	11	13.4	6.7	460-3	5,10,15,20	74	48 ⁵ / ₁₆	39 ⁷ / ₈	78.3	670
DFH0607D000001S	58,000	1,840	54,000	11	13.4	6.7	575-3	5,10,15,20	74	48 ⁵ / ₁₆	39 ⁷ / ₈	78.3	670

¹ BTU/h | Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.

DFH – Standard-Efficiency Air Conditioner Direct-Drive 6 Tons



*Complete warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

The Daikin DFH Commercial Packaged Air Conditioners feature high-efficiency scroll compressors, and easy access for servicing. These units are housed in a heavy-gauge, galvanized-steel cabinet with UV-resistant powder-paint finish.



DESIGNED FOR EXCEPTIONAL DURABILITY, ENERGY EFFICIENCY, AND OUTSTANDING PERFORMANCE.

- » R-410A chlorine-free refrigerant
- » Direct-Drive supply fan
- » Copper tube/aluminum fin coils and Micro Channel condensers
- » Screw on style pressure switches for ease of replacement
- » 24-volt Electromechanical controls package
- » Easy accessibility using our tool-less filter access
- » Convertible airflow orientation to serve downflow or horizontal applications
- » AHRI Certified; ETL Listed
- » Built to be a direct replacement for most rooftop units without the need of a curb adapter

Model	Nominal Capacities ¹			EER	IEER	COP-47	Voltage-Phase	Electric Heat (kW)	Dimensions			Sound Level dB(A)	Ship Weight (lbs)
	Cooling	CFM	Heating						W"	D"	H"		
DFH0723D000001S	68,000	2,350	67,000	11	14.5	3.4	208/230-3	5,10,15,20,30	74	48 ⁵ / ₁₆	43½	81.5	715
DFH0724D000001S	68,000	2,350	67,000	11	14.5	3.4	460-3	5,10,15,20,30	74	48 ⁵ / ₁₆	43½	81.5	715
DFH0727D000001S	68,000	2,350	67,000	11	14.5	3.4	575-3	5,10,15,20,30	74	48 ⁵ / ₁₆	43½	81.5	715
DFH0723W000001F	68,000	2,350	67,000	11	14.5	3.4	208/230-3	5,10,15,20,30	74	48 ⁵ / ₁₆	43½	81.5	719
DFH0724W000001F	68,000	2,350	67,000	11	14.5	3.4	460-3	5,10,15,20,30	74	48 ⁵ / ₁₆	43½	81.5	719
DFH0727W000001F	68,000	2,350	67,000	11	14.5	3.4	575-3	5,10,15,20,30	74	48 ⁵ / ₁₆	43½	81.5	719

¹ BTU/h | Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.



DFH – Standard-Efficiency Heat Pump Direct-Drive 7½ to 10 Tons



*Complete warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

The Daikin DFH Commercial Packaged Heat Pumps feature high-efficiency scroll compressors, two-stage cooling, and easy access for servicing. These units are housed in a heavy-gauge, galvanized-steel cabinet with UV-resistant powder-paint finish.



DESIGNED FOR EXCEPTIONAL DURABILITY, ENERGY EFFICIENCY, AND OUTSTANDING PERFORMANCE.

- » R-410A chlorine-free refrigerant
- » Two (2) single-stage scroll compressors individually circuited
- » Direct-Drive supply fan
- » Copper tube/aluminum fin coils and Micro Channel condensers
- » 24-volt Electromechanical controls package
- » Easy accessibility using our tool-less filter access
- » Screw on style pressure switches for ease of replacement
- » Convertible airflow orientation to serve downflow or horizontal applications
- » AHRI Certified; ETL Listed
- » Built to be a direct replacement for most rooftop units without the need of a curb adapter

Model	Nominal Capacities ¹				EER / IEER	COP-47	Voltage-Phase	Electric Heat (kW)	Dimensions			Sound Level dB(A)	Ship Weight (lbs)
	Cooling	CFM	Heating CAP 47F btu/hr	Heating CAP 17F btu/hr					W"	D"	H"		
DFH0903D000001S	86,000	3,000	85,000	49,000	11/14.1	3.4	208/230-3	15,30,45	90%	60%	54%	86.8	1200
DFH0904D000001S	86,000	3,000	85,000	49,000	11/14.1	3.4	460-3	15,30,45	90%	60%	54%	86.8	1200
DFH0907D000001S	86,000	3,000	85,000	49,000	11/14.1	3.4	575-3	15,30,45	90%	60%	54%	86.8	1200
DFH1023D000001S	100,000	3,000	100,000	61,000	11/14.1	3.4	208/230-3	15,30,45	90%	60%	54%	83.7	1214
DFH1024D000001S	100,000	3,000	100,000	61,000	11/14.1	3.4	460-3	15,30,45	90%	60%	54%	83.7	1214
DFH1027D000001S	100,000	3,000	100,000	61,000	11/14.1	3.4	575-3	15,30,45	90%	60%	54%	83.7	1214
DFH1203D000001S	116,000	3,850	116,000	65,000	11/14.1	3.4	208/230-3	15,30,45	90%	60%	54%	86.8	1234
DFH1204D000001S	116,000	3,850	116,000	65,000	11/14.1	3.4	460-3	15,30,45	90%	60%	54%	86.8	1234
DFH1207D000001S	116,000	3,850	116,000	65,000	11/14.1	3.4	575-3	15,30,45	90%	60%	54%	86.8	1234

¹ BTU/h | Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.



*Complete warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

DRH – High-Efficiency Heat Pump Direct-Drive 3 to 5 Tons



The Daikin DRH Commercial Packaged Heat Pumps feature high-efficiency scroll compressors, two-stage cooling, and easy access for servicing. These units are housed in a heavy-gauge, galvanized-steel cabinet with UV-resistant powder-paint finish.

DESIGNED FOR EXCEPTIONAL DURABILITY, ENERGY EFFICIENCY, AND OUTSTANDING PERFORMANCE.

- » R-410A chlorine-free refrigerant
- » Two-stage scroll compressor for partial load applications
- » ECM Direct-Drive supply fan
- » Copper tube/aluminum fin coils and Micro Channel condensers
- » 24-volt Electromechanical controls package
- » Easy accessibility using our tool-less filter access
- » Convertible airflow orientation to serve downflow or horizontal applications
- » AHRI Certified; ETL Listed
- » Built to be a direct replacement for most rooftop units without the need of a curb adapter

Model	Nominal Capacities ¹				EER2 / SEER2	HSPF2	Voltage-Phase	Electric Heat (kW)	Dimensions			Sound Level dB(A)	Ship Weight (lbs)
	Cooling	CFM	Heating CAP 47F btu/hr	Heating CAP 17F btu/hr					W"	D"	H"		
DRH0361D000001S	36,000	1200	33,400	20,000	12/16.2	7.4	208/230-1	5,10,15	74	48 ⁵ / ₁₆	39 ⁷ / ₈	75	766
DRH0363D000001S	36,000	1200	36,000	20,000	12/16.2	7.4	208/230-3	5,10,15	74	48 ⁵ / ₁₆	39 ⁷ / ₈	75	766
DRH0364D000001S	36,000	1200	36,000	20,000	12/16.2	7.4	460-3	5,10,15	74	48 ⁵ / ₁₆	39 ⁷ / ₈	75	766
DRH0367D000001S	36,000	1200	36,000	20,000	12/16.2	7.4	575-3	5,10,15	74	48 ⁵ / ₁₆	39 ⁷ / ₈	75	766
DRH0481D000001S	46,000	1,600	47,000	29,000	12/16.2	7.4	208/230-1	5,10,15,20	74	48 ⁵ / ₁₆	39 ⁷ / ₈	73	679
DRH0483D000001S	48,000	1,600	48,000	29,000	12/16.2	7.4	208/230-3	5,10,15,20	74	48 ⁵ / ₁₆	39 ⁷ / ₈	73	679
DRH0484D000001S	48,000	1,600	48,000	29,000	12/16.2	7.4	460-3	5,10,15,20	74	48 ⁵ / ₁₆	39 ⁷ / ₈	73	679
DRH0487D000001S	48,000	1,600	48,000	29,000	12/16.2	7.4	575-3	5,10,15,20	74	48 ⁵ / ₁₆	39 ⁷ / ₈	73	679
DRH0601D000001S	58,000	1,850	54,000	33,000	11.7/16	7.4	208/230-1	5,10,15,20	74	48 ⁵ / ₁₆	39 ⁷ / ₈	76	688
DRH0603D000001S	59,000	1,850	59,000	33,000	11.7/16	7.4	208/230-3	5,10,15,20	74	48 ⁵ / ₁₆	39 ⁷ / ₈	76	688
DRH0604D000001S	59,000	1,850	59,000	33,000	11.7/16	7.4	460-3	5,10,15,20	74	48 ⁵ / ₁₆	39 ⁷ / ₈	76	688
DRH0607D000001S	59,000	1,850	59,000	33,000	11.7/16	7.4	575-3	5,10,15,20	74	48 ⁵ / ₁₆	39 ⁷ / ₈	76	688

¹ BTU/h | Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.

DRH – High-Efficiency Heat Pump Direct-Drive 6 Tons



*Complete warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

The Daikin DRH Commercial Packaged Heat Pumps feature high-efficiency scroll compressors, two-stage cooling, and easy access for servicing. These units are housed in a heavy-gauge, galvanized-steel cabinet with UV-resistant powder-paint finish.



DESIGNED FOR EXCEPTIONAL DURABILITY, ENERGY EFFICIENCY, AND OUTSTANDING PERFORMANCE.

- | | | |
|---|--|--|
| » R-410A chlorine-free refrigerant | » Copper tube/aluminum fin coils on condenser and evaporator | » Convertible airflow orientation to serve downflow or horizontal applications |
| » Two-stage scroll compressor for partial load applications | » 24-volt Electromechanical controls package | » AHRI Certified; ETL Listed |
| » ECM Direct-Drive supply fan | » Easy accessibility using our tool-less filter access | » Built to be a direct replacement for most rooftop units without the need of a curb adapter |

Model	Nominal Capacities ¹				EER / IEER	COP-47	Voltage-Phase	Electric Heat (kW)	Dimensions			Sound Level dB(A)	Ship Weight (lbs)
	Cooling	CFM	Heating CAP 47F btu/hr	Heating CAP 17F btu/hr					W"	D"	H"		
DRH0723D000001S	69,000	2,200	61,000	33,000	11.5/17	3.4	208/230-3	5,10,15,20,30	74	48 ⁵ / ₁₆	53 ³ / ₄	81	766
DRH0724D000001S	69,000	2,200	61,000	33,000	11.5/17	3.4	460-3	5,10,15,20,30	74	48 ⁵ / ₁₆	53 ³ / ₄	81	766
DRH0727D000001S	69,000	2,200	61,000	33,000	11.5/17	3.4	575-3	5,10,15,20,30	74	48 ⁵ / ₁₆	53 ³ / ₄	81	766

¹ BTU/h | Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.



*Complete warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

DFG – Standard-Efficiency Gas/Electric Direct-Drive 3 to 5 Tons



The Daikin DFG Commercial Packaged Gas/Electric feature high-efficiency scroll compressors, two-stage cooling, and easy access for servicing. These units are housed in a heavy-gauge, galvanized-steel cabinet with UV-resistant powder-paint finish.

DESIGNED FOR EXCEPTIONAL DURABILITY, ENERGY EFFICIENCY, AND OUTSTANDING PERFORMANCE.

- » R-410A chlorine-free refrigerant
- » Direct-Drive supply fan
- » Copper tube/aluminum fin coils and Micro Channel condensers
- » Wrinkle Bend Technology on gas heat exchangers
- » Furnace in-shot gas burner manifold/ Ultra-low NOx burner technology
- » 24-volt Electromechanical controls package
- » Easy accessibility using our tool-less filter access
- » Screw on style pressure switches for ease of replacement
- » Convertible airflow orientation to serve downflow or horizontal applications
- » AHRI Certified; ETL Listed
- » Built to be a direct replacement for most rooftop units without the need of a curb adapter

Model	Nominal Capacities ¹			EER2 /SEER2	Voltage-Phase	Dimensions			Sound Level dB(A)	Ship Weight (lbs)
	Cooling	CFM	Heating			W"	D"	H"		
DFG0361DL00001S	35,000	1,160	45,000	11/13.4	208/230-1	73⅝	47⅞	39⅞	73	570
DFG0361DH00001S	35,000	1,160	90,000	11/13.4	208/230-1	73⅝	47⅞	39⅞	73	582
DFG0363DL00001S	35,000	1,160	45,000	11/13.4	208/230-3	73⅝	47⅞	39⅞	73	568
DFG0363DM00001S	35,000	1,160	70,000	11/13.4	208/230-3	73⅝	47⅞	39⅞	73	574
DFG0363DH00001S	35,000	1,160	90,000	11/13.4	208/230-3	73⅝	47⅞	39⅞	73	580
DFG0364DL00001S	35,000	1,160	45,000	11/13.4	460-3	73⅝	47⅞	39⅞	73	576
DFG0364DM00001S	35,000	1,160	70,000	11/13.4	460-3	73⅝	47⅞	39⅞	73	581
DFG0364DH00001S	35,000	1,160	90,000	11/13.4	460-3	73⅝	47⅞	39⅞	73	586
DFG0367DH00001S	35,000	1,160	90,000	11/13.4	575-3	73⅝	47⅞	39⅞	73	586
DFG0481DL00001S	47,000	1,570	90,000	11/13.4	208/230-1	73⅝	47⅞	39⅞	78.4	607
DFG0481DH00001S	47,000	1,570	115,000	11/13.4	208/230-1	73⅝	47⅞	39⅞	78.4	623
DFG0483DL00001S	47,000	1,570	70,000	11/13.4	208/230-3	73⅝	47⅞	39⅞	78.4	602
DFG0483DM00001S	47,000	1,570	90,000	11/13.4	208/230-3	73⅝	47⅞	39⅞	78.4	610
DFG0483DH00001S	47,000	1,570	115,000	11/13.4	208/230-3	73⅝	47⅞	39⅞	78.4	618
DFG0484DL00001S	47,000	1,570	70,000	11/13.4	460-3	73⅝	47⅞	39⅞	78.4	606
DFG0484DM00001S	47,000	1,570	90,000	11/13.4	460-3	73⅝	47⅞	39⅞	78.4	614
DFG0484DH00001S	47,000	1,570	115,000	11/13.4	460-3	73⅝	47⅞	39⅞	78.4	622
DFG0487DH00001S	47,000	1,570	115,000	11/13.4	575-3	73⅝	47⅞	39⅞	78.4	622
DFG0601DL00001S	59,000	1,820	90,000	11/13.4	208/230-1	73⅝	47⅞	39⅞	78.3	611
DFG0601DH00001S	59,000	1,820	140,000	11/13.4	208/230-1	73⅝	47⅞	39⅞	78.3	628
DFG0603DL00001S	59,000	1,820	90,000	11/13.4	208/230-3	73⅝	47⅞	39⅞	78.3	607
DFG0603DM00001S	59,000	1,820	115,000	11/13.4	208/230-3	73⅝	47⅞	39⅞	78.3	620
DFG0603DH00001S	59,000	1,820	140,000	11/13.4	208/230-3	73⅝	47⅞	39⅞	78.3	624
DFG0604DL00001S	59,000	1,820	90,000	11/13.4	460-3	73⅝	47⅞	39⅞	78.3	611
DFG0604DM00001S	59,000	1,820	115,000	11/13.4	460-3	73⅝	47⅞	39⅞	78.3	624
DFG0604DH00001S	59,000	1,820	140,000	11/13.4	460-3	73⅝	47⅞	39⅞	78.3	628
DFG0607DH00001S	59,000	1,820	140,000	11/13.4	575-3	73⅝	47⅞	39⅞	78.3	628

¹ BTU/h | Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.

DFG – Standard-Efficiency Gas/Electric Direct-Drive Ultra Low No_x 3 to 5 Tons (cont.)



*Complete warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

Model	Nominal Capacities¹			EER2 / SEER2	Voltage-Phase	Dimensions			Sound Level dB(A)	Ship Weight (lbs)
	Cooling	CFM	Heating			W"	D"	H"		
ULN Models										
DFG0361D600001F	35,000	1,160	60,000	11/13.4	208/230-1	73⅜	47⅞	39⅞	73	576
DFG0361D800001F	35,000	1,160	80,000	11/13.4	208/230-1	73⅜	47⅞	39⅞	73	582
DFG0361D100001F	35,000	1,160	100,000	11/13.4	208/230-1	73⅜	47⅞	39⅞	73	589
DFG0363D600001F	35,000	1,160	60,000	11/13.4	208/230-3	73⅜	47⅞	39⅞	73	574
DFG0363D800001F	35,000	1,160	80,000	11/13.4	208/230-3	73⅜	47⅞	39⅞	73	580
DFG0363D100001F	35,000	1,160	100,000	11/13.4	208/230-3	73⅜	47⅞	39⅞	73	587
DFG0364D600001F	35,000	1,160	60,000	11/13.4	460-3	73⅜	47⅞	39⅞	73	581
DFG0364D800001F	35,000	1,160	80,000	11/13.4	460-3	73⅜	47⅞	39⅞	73	586
DFG0364D100001F	35,000	1,160	100,000	11/13.4	460-3	73⅜	47⅞	39⅞	73	590
DFG0481DH80001F	47,000	1,570	80,000	11/13.4	208/230-1	73⅜	47⅞	39⅞	78.4	607
DFG0481D100001F	47,000	1,570	100,000	11/13.4	208/230-1	73⅜	47⅞	39⅞	78.4	623
DFG0483D800001F	47,000	1,570	80,000	11/13.4	208/230-3	73⅜	47⅞	39⅞	78.4	610
DFG0483D100001F	47,000	1,570	100,000	11/13.4	208/230-3	73⅜	47⅞	39⅞	78.4	618
DFG0484D800001F	47,000	1,570	80,000	11/13.4	460-3	73⅜	47⅞	39⅞	78.4	614
DFG0484D100001F	47,000	1,570	100,000	11/13.4	460-3	73⅜	47⅞	39⅞	78.4	622
DFG0601D1000001F	59,000	1,820	100,000	11/13.4	208/230-1	73⅜	47⅞	39⅞	78.3	624
DFG0601D8000001F	59,000	1,820	80,000	11/13.4	208/230-1	73⅜	47⅞	39⅞	78.3	611
DFG0603D1000001F	59,000	1,820	100,000	11/13.4	208/230-3	73⅜	47⅞	39⅞	78.3	620
DFG0603D8000001F	59,000	1,820	80,000	11/13.4	208/230-3	73⅜	47⅞	39⅞	78.3	607
DFG0604D1000001F	59,000	1,820	100,000	11/13.4	460-3	73⅜	47⅞	39⅞	78.3	624
DFG0604D8000001F	59,000	1,820	80,000	11/13.4	460-3	73⅜	47⅞	39⅞	78.3	611

¹ BTU/h | Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.



*Complete warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

DFG – Standard-Efficiency Gas/Electric Direct-Drive 6 Tons



The Daikin DFG Commercial Packaged Gas/Electric feature high-efficiency scroll compressors, two-stage cooling, and easy access for servicing. These units are housed in a heavy-gauge, galvanized-steel cabinet with UV-resistant powder-paint finish.

DESIGNED FOR EXCEPTIONAL DURABILITY, ENERGY EFFICIENCY, AND OUTSTANDING PERFORMANCE.

- » R-410A chlorine-free refrigerant
- » Two-stage scroll compressor
- » Direct-Drive supply fan
- » Copper tube/aluminum fin coils and Micro Channel condensers
- » Screw on style pressure switches for ease of replacement
- » Wrinkle Bend Technology on gas heat exchangers
- » 24-volt Electromechanical controls package
- » Easy accessibility using our tool-less filter access
- » Convertible airflow orientation to serve downflow or horizontal applications
- » AHRI Certified; ETL Listed
- » Built to be a direct replacement for most rooftop units without the need of a curb adapter

Model	Nominal Capacities ¹			EER / IEER	Voltage-Phase	Dimensions			Sound Level dB(A)	Ship Weight (lbs)
	Cooling	CFM	Heating			W"	D"	H"		
DFG0723DL00001S	69,000	2100	90,000	11.2/15.5	208/230-3	73¾	47¾	39¾	82	680
DFG0723DM00001S	69,000	2100	115,000	11.2/15.5	208/230-3	73¾	47¾	39¾	82	688
DFG0723DH00001S	69,000	2100	140,000	11.2/15.5	208/230-3	73¾	47¾	39¾	82	696
DFG0724DL00001S	69,000	2100	90,000	11.2/15.5	460-3	73¾	47¾	39¾	82	680
DFG0724DM00001S	69,000	2100	115,000	11.2/15.5	460-3	73¾	47¾	39¾	82	688
DFG0724DH00001S	69,000	2100	140,000	11.2/15.5	460-3	73¾	47¾	39¾	82	696
DFG0727DL00001S	69,000	2100	90,000	11.2/15.5	575-3	73¾	47¾	39¾	82	680
DFG0727DM00001S	69,000	2100	115,000	11.2/15.5	575-3	73¾	47¾	39¾	82	688
DFG0727DH00001S	69,000	2100	140,000	11.2/15.5	575-3	73¾	47¾	39¾	82	696
DFG0723WL00001F	69,000	2100	90,000	11.2/15.5	208/230-3	73¾	47¾	39¾	82	684
DFG0723WM00001F	69,000	2100	115,000	11.2/15.5	208/230-3	73¾	47¾	39¾	82	692
DFG0723VH00001F	69,000	2100	140,000	11.2/15.5	208/230-3	73¾	47¾	39¾	82	700
DFG0724WL00001F	69,000	2100	90,000	11.2/15.5	460-3	73¾	47¾	39¾	82	684
DFG0724WM00001F	69,000	2100	115,000	11.2/15.5	460-3	73¾	47¾	39¾	82	692
DFG0724VH00001F	69,000	2100	140,000	11.2/15.5	460-3	73¾	47¾	39¾	82	700
DFG0727WL00001F	69,000	2100	90,000	11.2/15.5	575-3	73¾	47¾	39¾	82	684
DFG0727WM00001F	69,000	2100	115,000	11.2/15.5	575-3	73¾	47¾	39¾	82	692
DFG0727VH00001F	69,000	2100	140,000	11.2/15.5	575-3	73¾	47¾	39¾	82	700

¹ BTU/h | Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.

LIGHT COMMERCIAL

DFG – Standard-Efficiency Gas/Electric Direct-Drive 7½ to 12½ Tons



*Complete warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

The Daikin DFG Commercial Packaged Gas/Electric Units feature the chlorine-free refrigerant R-410A. Other features include our dual-diameter tubular heat exchanger and a high-efficiency scroll compressor. These units are housed in a heavy-gauge, galvanized-steel cabinet with UV-resistant powder-paint finish.



DESIGNED FOR EXCEPTIONAL DURABILITY, ENERGY EFFICIENCY, AND OUTSTANDING PERFORMANCE.

- » R-410A chlorine-free refrigerant
- » Two (2) single-stage scroll compressors individually circuited
- » Direct-Drive supply fan
- » Copper tube/aluminum fin coils and Micro Channel condensers
- » Wrinkle Bend Technology on gas heat exchangers
- » 24-volt Electromechanical controls package
- » Easy accessibility using our tool-less filter access
- » Screw on style pressure switches for ease of replacement
- » Convertible airflow orientation to serve downflow or horizontal applications
- » AHRI Certified; ETL Listed
- » Built to be a direct replacement for most rooftop units without the need of a curb adapter

Model	Nominal Capacities ¹			EER / IEER	Voltage-Phase	Dimensions			Sound Level dB(A)	Ship Weight (lbs)
	Cooling	CFM	Heating			W"	D"	H"		
DFG0903DL00001S	86,000	3,020	130,000	11.2/14.8	208/230-3	90 $\frac{3}{8}$	60 $\frac{3}{16}$	54 $\frac{5}{8}$	82.6	1120
DFG0903DM00001S	86,000	3,020	180,000	11.2/14.8	208/230-3	90 $\frac{3}{8}$	60 $\frac{3}{16}$	54 $\frac{5}{8}$	82.6	1130
DFG0903DH00001S	86,000	3,020	225,000	11.2/14.8	208/230-3	90 $\frac{3}{8}$	60 $\frac{3}{16}$	54 $\frac{5}{8}$	82.6	1140
DFG0904DL00001S	86,000	3,020	130,000	11.2/14.8	460-3	90 $\frac{3}{8}$	60 $\frac{3}{16}$	54 $\frac{5}{8}$	82.6	1120
DFG0904DM00001S	86,000	3,020	180,000	11.2/14.8	460-3	90 $\frac{3}{8}$	60 $\frac{3}{16}$	54 $\frac{5}{8}$	82.6	1130
DFG0904DH00001S	86,000	3,020	225,000	11.2/14.8	460-3	90 $\frac{3}{8}$	60 $\frac{3}{16}$	54 $\frac{5}{8}$	82.6	1140
DFG0907DL00001S	86,000	3,020	130,000	11.2/14.8	575-3	90 $\frac{3}{8}$	60 $\frac{3}{16}$	54 $\frac{5}{8}$	82.6	1120
DFG0907DM00001S	86,000	3,020	180,000	11.2/14.8	575-3	90 $\frac{3}{8}$	60 $\frac{3}{16}$	54 $\frac{5}{8}$	82.6	1130
DFG0907DH00001S	86,000	3,020	225,000	11.2/14.8	575-3	90 $\frac{3}{8}$	60 $\frac{3}{16}$	54 $\frac{5}{8}$	82.6	1140
DFG1023DL00001S	97,000	3,230	130,000	11.2/14.8	208/230-3	90 $\frac{3}{8}$	60 $\frac{3}{16}$	54 $\frac{5}{8}$	82.6	1140
DFG1023DM00001S	97,000	3,230	180,000	11.2/14.8	208/230-3	90 $\frac{3}{8}$	60 $\frac{3}{16}$	54 $\frac{5}{8}$	82.6	1150
DFG1023DH00001S	97,000	3,230	225,000	11.2/14.8	208/230-3	90 $\frac{3}{8}$	60 $\frac{3}{16}$	54 $\frac{5}{8}$	82.6	1160
DFG1024DL00001S	97,000	3,230	130,000	11.2/14.8	460-3	90 $\frac{3}{8}$	60 $\frac{3}{16}$	54 $\frac{5}{8}$	82.6	1140
DFG1024DM00001S	97,000	3,230	180,000	11.2/14.8	460-3	90 $\frac{3}{8}$	60 $\frac{3}{16}$	54 $\frac{5}{8}$	82.6	1150
DFG1024DH00001S	97,000	3,230	225,000	11.2/14.8	460-3	90 $\frac{3}{8}$	60 $\frac{3}{16}$	54 $\frac{5}{8}$	82.6	1160
DFG1027DL00001S	97,000	3,230	130,000	11.2/14.8	575-3	90 $\frac{3}{8}$	60 $\frac{3}{16}$	54 $\frac{5}{8}$	82.6	1140
DFG1027DM00001S	97,000	3,230	180,000	11.2/14.8	575-3	90 $\frac{3}{8}$	60 $\frac{3}{16}$	54 $\frac{5}{8}$	82.6	1150
DFG1027DH00001S	97,000	3,230	225,000	11.2/14.8	575-3	90 $\frac{3}{8}$	60 $\frac{3}{16}$	54 $\frac{5}{8}$	82.6	1160
DFG1203DL00001S	116,000	3,380	130,000	11.2/14.8	208/230-3	90 $\frac{3}{8}$	60 $\frac{3}{16}$	54 $\frac{5}{8}$	82.6	1199
DFG1203DM00001S	116,000	3,380	180,000	11.2/14.8	208/230-3	90 $\frac{3}{8}$	60 $\frac{3}{16}$	54 $\frac{5}{8}$	82.6	1209
DFG1203DH00001S	116,000	3,380	240,000	11.2/14.8	208/230-3	90 $\frac{3}{8}$	60 $\frac{3}{16}$	54 $\frac{5}{8}$	82.6	1219
DFG1204DL00001S	116,000	3,380	130,000	11.2/14.8	460-3	90 $\frac{3}{8}$	60 $\frac{3}{16}$	54 $\frac{5}{8}$	82.6	1199
DFG1204DM00001S	116,000	3,380	180,000	11.2/14.8	460-3	90 $\frac{3}{8}$	60 $\frac{3}{16}$	54 $\frac{5}{8}$	82.6	1209

DFG – Standard-Efficiency Gas/Electric Direct-Drive 7½ to 12½ Tons (cont.)

Model	Nominal Capacities ¹			EER / IEER	Voltage-Phase	Dimensions			Sound Level dB(A)	Ship Weight (lbs)
	Cooling	CFM	Heating			W"	D"	H"		
DFG1204DH00001S	116,000	3,380	240,000	11.2/14.8	460-3	90⅝	60 ⅜ ₁₆	54⅝	82.6	1219
DFG1207DL00001S	116,000	3,380	130,000	11.2/14.8	575-3	90⅝	60 ⅜ ₁₆	54⅝	82.6	1199
DFG1207DM00001S	116,000	3,380	180,000	11.2/14.8	575-3	90⅝	60 ⅜ ₁₆	54⅝	82.6	1209
DFG1207DH00001S	116,000	3,380	240,000	11.2/14.8	575-3	90⅝	60 ⅜ ₁₆	54⅝	82.6	1219
DFG1503DL00001S	140,000	4,200	130,000	11/14.2	208/230-3	90⅝	60 ⅜ ₁₆	54⅝	86.8	1290
DFG1503DM00001S	140,000	4,200	180,000	11/14.2	208/230-3	90⅝	60 ⅜ ₁₆	54⅝	86.8	1300
DFG1503DH00001S	140,000	4,200	240,000	11/14.2	208/230-3	90⅝	60 ⅜ ₁₆	54⅝	86.8	1310
DFG1504DL00001S	140,000	4,200	130,000	11/14.2	460-3	90⅝	60 ⅜ ₁₆	54⅝	86.8	1290
DFG1504DM00001S	140,000	4,200	180,000	11/14.2	460-3	90⅝	60 ⅜ ₁₆	54⅝	86.8	1300
DFG1504DH00001S	140,000	4,200	240,000	11/14.2	460-3	90⅝	60 ⅜ ₁₆	54⅝	86.8	1310
DFG1507DL00001S	140,000	4,200	130,000	11/14.2	575-3	90⅝	60 ⅜ ₁₆	54⅝	86.8	1290
DFG1507DM00001S	140,000	4,200	180,000	11/14.2	575-3	90⅝	60 ⅜ ₁₆	54⅝	86.8	1300
DFG1507DH00001S	140,000	4,200	240,000	11/14.2	575-3	90⅝	60 ⅜ ₁₆	54⅝	86.8	1310
DFG1503LL00001F	140,000	4,200	130,000	11/14.2	208/230-3	90⅝	60 ⅜ ₁₆	54⅝	86.8	1290
DFG1503LM00001F	140,000	4,200	180,000	11/14.2	208/230-3	90⅝	60 ⅜ ₁₆	54⅝	86.8	1300
DFG1503LH00001F	140,000	4,200	240,000	11/14.2	208/230-3	90⅝	60 ⅜ ₁₆	54⅝	86.8	1310
DFG1504LL00001F	140,000	4,200	130,000	11/14.2	460-3	90⅝	60 ⅜ ₁₆	54⅝	86.8	1290
DFG1504LM00001F	140,000	4,200	180,000	11/14.2	460-3	90⅝	60 ⅜ ₁₆	54⅝	86.8	1300
DFG1504LH00001F	140,000	4,200	240,000	11/14.2	460-3	90⅝	60 ⅜ ₁₆	54⅝	86.8	1310
DFG1507LL00001F	140,000	4,200	130,000	11/14.2	575-3	90⅝	60 ⅜ ₁₆	54⅝	86.8	1290
DFG1507LM00001F	140,000	4,200	180,000	11/14.2	575-3	90⅝	60 ⅜ ₁₆	54⅝	86.8	1300
DFG1507LH00001F	140,000	4,200	240,000	11/14.2	575-3	90⅝	60 ⅜ ₁₆	54⅝	86.8	1310

¹ BTU/h | Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.

DFG – Base-Efficiency Gas/Electric Direct-Drive 15 to 25 Tons



*Complete warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

The Daikin DFG Commercial Packaged Gas/Electric Units feature the chlorine-free refrigerant R-410A. Other features include our dual-diameter tubular heat exchanger and a high-efficiency scroll compressor. These units are housed in a heavy-gauge, galvanized-steel cabinet with UV-resistant powder-paint finish.



DESIGNED FOR EXCEPTIONAL DURABILITY, ENERGY EFFICIENCY, AND OUTSTANDING PERFORMANCE.

- » R-410A chlorine-free refrigerant
- » Two (2) single-stage scroll compressors individually circuited
- » Two (2) direct-drive supply fans
- » Copper tube/aluminum fin coils and Micro Channel condensers
- » Wrinkle Bend Technology available on gas heat exchangers
- » 24-volt Electromechanical controls package
- » Dedicated downflow orientation convertible with an adapter.
- » AHRI Certified; ETL Listed
- » Screw on style pressure switches for ease of replacement

Model	Nominal Capacities ¹			EER / IEER	Voltage-Phase	Dimensions			Sound Level dB(A)	Ship Weight (lbs)
	Cooling	CFM	Heating			W"	D"	H"		
DFG1803DL00001S	172,000	5,000	260,000	10.8/14	208/230-3	133 7/8	88½	51⅔	80.4	2025
DFG1803DM00001S	172,000	5,000	360,000	10.8/14	208/230-3	133 7/8	88½	51⅔	80.4	2025
DFG1803DH00001S	172,000	5,000	400,000	10.8/14	208/230-3	133 7/8	88½	51⅔	80.4	2025
DFG1804DL00001S	172,000	5,000	260,000	10.8/14	460-3	133 7/8	88½	51⅔	80.4	2025
DFG1804DM00001S	172,000	5,000	360,000	10.8/14	460-3	133 7/8	88½	51⅔	80.4	2025
DFG1804DH00001S	172,000	5,000	400,000	10.8/14	460-3	133 7/8	88½	51⅔	80.4	2025
DFG1807DL00001S	172,000	5,000	260,000	10.8/14	575-3	133 7/8	88½	51⅔	80.4	2025
DFG1807DM00001S	172,000	5,000	360,000	10.8/14	575-3	133 7/8	88½	51⅔	80.4	2025
DFG1807DH00001S	172,000	5,000	400,000	10.8/14	575-3	133 7/8	88½	51⅔	80.4	2025
DFG2403DL00001S	230,000	6,500	260,000	10.8/14	208/230-3	133 7/8	88½	51	92.1	2294
DFG2403DM00001S	230,000	6,500	360,000	10.8/14	208/230-3	133 7/8	88½	51	92.1	2294
DFG2403DH00001S	230,000	6,500	400,000	10.8/14	208/230-3	133 7/8	88½	51	92.1	2294
DFG2404DL00001S	230,000	6,500	260,000	10.8/14	460-3	133 7/8	88½	51	92.1	2294
DFG2404DM00001S	230,000	6,500	360,000	10.8/14	460-3	133 7/8	88½	51	92.1	2294
DFG2404DH00001S	230,000	6,500	400,000	10.8/14	460-3	133 7/8	88½	51	92.1	2294
DFG2407DL00001S	230,000	6,500	260,000	10.8/14	575-3	133 7/8	88½	51	92.1	2294
DFG2407DM00001S	230,000	6,500	360,000	10.8/14	575-3	133 7/8	88½	51	92.1	2294
DFG2407DH00001S	230,000	6,500	400,000	10.8/14	575-3	133 7/8	88½	51	92.1	2294
DFG3003DL00001S	290,000	8,200	260,000	9.8/13	208/230-3	133 7/8	88½	51	91.3	2385
DFG3003DM00001S	290,000	8,200	360,000	9.8/13	208/230-3	133 7/8	88½	51	91.3	2385
DFG3003DH00001S	290,000	8,200	400,000	9.8/13	208/230-3	133 7/8	88½	51	91.3	2385
DFG3004DL00001S	290,000	8,200	260,000	9.8/13	460-3	133 7/8	88½	51	91.3	2385
DFG3004DM00001S	290,000	8,200	360,000	9.8/13	460-3	133 7/8	88½	51	91.3	2385
DFG3004DH00001S	290,000	8,200	400,000	9.8/13	460-3	133 7/8	88½	51	91.3	2385
DFG3007DL00001S	290,000	8,200	260,000	9.8/13	575-3	133 7/8	88½	51	91.3	2385
DFG3007DM00001S	290,000	8,200	360,000	9.8/13	575-3	133 7/8	88½	51	91.3	2385
DFG3007DH00001S	290,000	8,200	400,000	9.8/13	575-3	133 7/8	88½	51	91.3	2385

¹ BTU/h | Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.



*Complete warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

DRG – High-Efficiency Gas/Electric Direct-Drive 3- 6 Tons



The Daikin DRG Commercial Packaged Gas/Electric Units feature the chlorine-free refrigerant R-410A. Other features include our dual-diameter tubular heat exchanger and a high-efficiency scroll compressor. These units are housed in a heavy-gauge, galvanized-steel cabinet with UV-resistant powder-paint finish.

DESIGNED FOR EXCEPTIONAL DURABILITY, ENERGY EFFICIENCY, AND OUTSTANDING PERFORMANCE.

- » R-410A chlorine-free refrigerant
- » Two-stage scroll compressor for partial load applications
- » ECM Direct-Drive supply fan
- » Copper tube/aluminum fin coils on condenser and evaporator
- » Wrinkle Bend Technology available on gas heat exchangers
- » 24-volt Electromechanical controls package
- » Easy accessibility using our tool-less filter access
- » Convertible airflow orientation to serve downflow or horizontal applications
- » AHRI Certified; ETL Listed
- » Built to be a direct replacement for most rooftop units without the need of a curb adapter

Model	Nominal Capacities ¹			EER2/SEER2	Voltage-Phase	Dimensions			Sound Level dB(A)	Ship Weight (lbs)
	Cooling	CFM	Heating			W"	D"	H"		
DRG0361DL00001S	36,000	1,200	45,000	12.1/16.4	208/230-1	74	48 ⁹ / ₁₆	39 ⁷ / ₈	75	630
DRG0361DM00001S	36,000	1,200	70,000	12.1/16.4	208/230-1	74	48 ⁹ / ₁₆	39 ⁷ / ₈	75	630
DRG0361DH00001S	36,000	1,200	115,000	12.1/16.4	208/230-1	74	48 ⁹ / ₁₆	39 ⁷ / ₈	75	630
DRG0363DL00001S	36,000	1,200	45,000	12.1/16.4	208/230-3	74	48 ⁹ / ₁₆	39 ⁷ / ₈	75	630
DRG0363DM00001S	36,000	1,200	70,000	12.1/16.4	208/230-3	74	48 ⁹ / ₁₆	39 ⁷ / ₈	75	630
DRG0363DH00001S	36,000	1,200	115,000	12.1/16.4	208/230-3	74	48 ⁹ / ₁₆	39 ⁷ / ₈	75	630
DRG0364DL00001S	36,000	1,200	45,000	12.1/16.4	460-3	74	48 ⁹ / ₁₆	39 ⁷ / ₈	75	630
DRG0364DM00001S	36,000	1,200	70,000	12.1/16.4	460-3	74	48 ⁹ / ₁₆	39 ⁷ / ₈	75	630
DRG0364DH00001S	36,000	1,200	115,000	12.1/16.4	460-3	74	48 ⁹ / ₁₆	39 ⁷ / ₈	75	630
DRG0367DL00001S	36,000	1,200	45,000	12.1/16.4	575-3	74	48 ⁹ / ₁₆	39 ⁷ / ₈	75	630
DRG0367DM00001S	36,000	1,200	70,000	12.1/16.4	575-3	74	48 ⁹ / ₁₆	39 ⁷ / ₈	75	630
DRG0367DH00001S	36,000	1,200	115,000	12.1/16.4	575-3	74	48 ⁹ / ₁₆	39 ⁷ / ₈	75	630
DRG0481DL00001S	47,000	1,600	70,000	12/16.4	208/230-1	74	48 ⁹ / ₁₆	43 ¹ / ₂	73	705
DRG0481DM00001S	47,000	1,600	115,000	12/16.4	208/230-1	74	48 ⁹ / ₁₆	43 ¹ / ₂	73	705
DRG0481DH00001S	47,000	1,600	140,000	12/16.4	208/230-1	74	48 ⁹ / ₁₆	43 ¹ / ₂	73	705
DRG0483DL00001S	48,000	1,600	70,000	12/16.4	208/230-3	74	48 ⁹ / ₁₆	43 ¹ / ₂	73	705
DRG0483DM00001S	48,000	1,600	115,000	12/16.4	208/230-3	74	48 ⁹ / ₁₆	43 ¹ / ₂	73	705
DRG0483DH00001S	48,000	1,600	140,000	12/16.4	208/230-3	74	48 ⁹ / ₁₆	43 ¹ / ₂	73	705
DRG0484DL00001S	48,000	1,600	70,000	12/16.4	460-3	74	48 ⁹ / ₁₆	43 ¹ / ₂	73	705
DRG0484DM00001S	48,000	1,600	115,000	12/16.4	460-3	74	48 ⁹ / ₁₆	43 ¹ / ₂	73	705
DRG0484DH00001S	48,000	1,600	140,000	12/16.4	460-3	74	48 ⁹ / ₁₆	43 ¹ / ₂	73	705
DRG0487DL00001S	48,000	1,600	70,000	12/16.4	575-3	74	48 ⁹ / ₁₆	43 ¹ / ₂	73	705
DRG0487DM00001S	48,000	1,600	115,000	12/16.4	575-3	74	48 ⁹ / ₁₆	43 ¹ / ₂	73	705
DRG0487DH00001S	48,000	1,600	140,000	12/16.4	575-3	74	48 ⁹ / ₁₆	43 ¹ / ₂	73	705

¹ BTU/h | Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.

DRG – High-Efficiency Gas/Electric Direct-Drive 3 to 6 Tons (cont.)



* Complete warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

Model	Nominal Capacities ¹			EER2/SEER2	Voltage-Phase	Dimensions			Sound Level dB(A)	Ship Weight (lbs)
	Cooling	CFM	Heating			W"	D"	H"		
DRG0601DL00001S	58,000	2,000	70,000	11.9/16.2	208/230-1	74	48 ⁵ / ₁₆	43 ¹ / ₂	76	713
DRG0601DM00001S	58,000	2,000	115,000	11.9/16.2	208/230-1	74	48 ⁵ / ₁₆	43 ¹ / ₂	76	713
DRG0601DH00001S	58,000	2,000	140,000	11.9/16.2	208/230-1	74	48 ⁵ / ₁₆	43 ¹ / ₂	76	713
DRG0603DL00001S	60,000	2,000	70,000	11.9/16.2	208/230-3	74	48 ⁵ / ₁₆	43 ¹ / ₂	76	713
DRG0603DM00001S	60,000	2,000	115,000	11.9/16.2	208/230-3	74	48 ⁵ / ₁₆	43 ¹ / ₂	76	713
DRG0603DH00001S	60,000	2,000	140,000	11.9/16.2	208/230-3	74	48 ⁵ / ₁₆	43 ¹ / ₂	76	713
DRG0604DL00001S	60,000	2,000	70,000	11.9/16.2	460-3	74	48 ⁵ / ₁₆	43 ¹ / ₂	76	713
DRG0604DM00001S	60,000	2,000	115,000	11.9/16.2	460-3	74	48 ⁵ / ₁₆	43 ¹ / ₂	76	713
DRG0604DH00001S	60,000	2,000	140,000	11.9/16.2	460-3	74	48 ⁵ / ₁₆	43 ¹ / ₂	76	713
DRG0607DL00001S	60,000	2,000	70,000	11.9/16.2	575-3	74	48 ⁵ / ₁₆	43 ¹ / ₂	76	713
DRG0607DM00001S	60,000	2,000	115,000	11.9/16.2	575-3	74	48 ⁵ / ₁₆	43 ¹ / ₂	76	713
DRG0607DH00001S	60,000	2,000	140,000	11.9/16.2	575-3	74	48 ⁵ / ₁₆	43 ¹ / ₂	76	713
ULN Models										
DRG0361D600001F	36,000	1,200	60,000	12.1/16.4	208/230-1	74	48 ⁵ / ₁₆	39 ⁷ / ₈	75	630
DRG0361D800001F	36,000	1,200	80,000	12.1/16.4	208/230-1	74	48 ⁵ / ₁₆	39 ⁷ / ₈	75	630
DRG0363D600001F	36,000	1,200	60,000	12.1/16.4	208/230-3	74	48 ⁵ / ₁₆	39 ⁷ / ₈	75	630
DRG0363D800001F	36,000	1,200	80,000	12.1/16.4	208/230-3	74	48 ⁵ / ₁₆	39 ⁷ / ₈	75	630
DRG0364D600001F	36,000	1,200	60,000	12.1/16.4	460-3	74	48 ⁵ / ₁₆	39 ⁷ / ₈	75	630
DRG0364D800001F	36,000	1,200	80,000	12.1/16.4	460-3	74	48 ⁵ / ₁₆	39 ⁷ / ₈	75	630
DRG0361D100001F	36,000	1,200	100,000	12.1/16.4	208/230-1	74	48 ⁵ / ₁₆	39 ⁷ / ₈	75	630
DRG0363D100001F	36,000	1,200	100,000	12.1/16.4	208/230-3	74	48 ⁵ / ₁₆	39 ⁷ / ₈	75	630
DRG0364D100001F	36,000	1,200	100,000	12.1/16.4	460-3	74	48 ⁵ / ₁₆	39 ⁷ / ₈	75	630
DRG0481D800001F	47,000	1,600	80,000	12/16.4	208/230-1	74	48 ⁵ / ₁₆	43 ¹ / ₂	73	705
DRG0483D800001F	48,000	1,600	80,000	12/16.4	208/230-3	74	48 ⁵ / ₁₆	43 ¹ / ₂	73	705
DRG0484D800001F	48,000	1,600	80,000	12/16.4	460-3	74	48 ⁵ / ₁₆	43 ¹ / ₂	73	705
DRG0481D100001F	47,000	1,600	100000	12/16.4	208/230-1	74	48 ⁵ / ₁₆	43 ¹ / ₂	73	705
DRG0483D100001F	48,000	1,600	100000	12/16.4	208/230-3	74	48 ⁵ / ₁₆	43 ¹ / ₂	73	705
DRG0484D100001F	48,000	1,600	100000	12/16.4	460-3	74	48 ⁵ / ₁₆	43 ¹ / ₂	73	705
DRG0601D800001F	58,000	2000	80,000	11.9/16.2	208/230-1	74	48 ⁵ / ₁₆	43 ¹ / ₂	76	713
DRG0603D800001F	60,000	2000	80,000	11.9/16.2	208/230-3	74	48 ⁵ / ₁₆	43 ¹ / ₂	76	713
DRG0604D800001F	60,000	2000	80,000	11.9/16.2	460-3	74	48 ⁵ / ₁₆	43 ¹ / ₂	76	713
DRG0601D100001F	58,000	2000	100000	11.9/16.2	208/230-1	74	48 ⁵ / ₁₆	43 ¹ / ₂	76	713
DRG0603D100001F	60,000	2000	100000	11.9/16.2	208/230-3	74	48 ⁵ / ₁₆	43 ¹ / ₂	76	713
DRG0604D100001F	60,000	2000	100000	11.9/16.2	460-3	74	48 ⁵ / ₁₆	43 ¹ / ₂	76	713

¹ BTU/h | Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.

Model	Nominal Capacities ¹			IEER / EER	Voltage-Phase	Dimensions			Sound Level dB(A)	Ship Weight (lbs)
	Cooling	CFM	Heating			W"	D"	H"		
DRG0723DM00001S	72,000	2,400	125,000	17.1/12.1	208/230-3	74	48 ⁵ / ₁₆	53 ³ / ₄	81	763
DRG0723DH00001S	72,000	2,400	150,000	17.1/12.1	208/230-3	74	48 ⁵ / ₁₆	53 ³ / ₄	81	763
DRG0724DL00001S	72,000	2,400	70,000	17.1/12.1	460-3	74	48 ⁵ / ₁₆	53 ³ / ₄	81	763
DRG0724DM00001S	72,000	2,400	125,000	17.1/12.1	460-3	74	48 ⁵ / ₁₆	53 ³ / ₄	81	763
DRG0724DH00001S	72,000	2,000	150,000	17.1/12.1	460-3	74	48 ⁵ / ₁₆	53 ³ / ₄	81	763
DRG0727DL00001S	72,000	2,400	70,000	17.1/12.1	575-3	74	48 ⁵ / ₁₆	53 ³ / ₄	81	763
DRG0727DM00001S	72,000	2,400	125,000	17.1/12.1	575-3	74	48 ⁵ / ₁₆	53 ³ / ₄	81	763
DRG0727DH00001S	72,000	2,400	150,000	17.1/12.1	575-3	74	48 ⁵ / ₁₆	53 ³ / ₄	81	763

¹ BTU/h | Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.



*Complete warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

DRG – High-Efficiency Gas/Electric Direct-Drive 7½ to 12½ Tons



The Daikin DRG Commercial Packaged Gas/Electric feature the chlorine-free refrigerant R-410A. Other features include a high-efficiency scroll compressor and easy access for servicing. These units are housed in a heavy-gauge, galvanized-steel cabinet with UV-resistant powder-paint finish.

DESIGNED FOR EXCEPTIONAL DURABILITY, ENERGY EFFICIENCY, AND OUTSTANDING PERFORMANCE.

- » R-410A chlorine-free refrigerant
- » Dual single-stage scroll compressor for partial load applications
- » ECM Direct-Drive supply fan
- » Copper tube/aluminum fin coils on condenser and evaporator
- » Wrinkle Bend Technology available on gas heat exchangers
- » 24-volt Electromechanical controls package
- » Easy accessibility using our tool-less filter access
- » Convertible airflow orientation to serve downflow or horizontal applications
- » AHRI Certified; ETL Listed
- » Built to be a direct replacement for most rooftop units without the need of a curb adapter

Model	Nominal Capacities ¹			EER / IEER	Voltage-Phase	Dimensions			Sound Level dB(A)	Ship Weight (lbs)
	Cooling	CFM	Heating			W"	D"	H"		
DRG0903DL00001S	90,000	3,000	130,000	12.2 / 16	208/230-3	93¾	60¾	54¾ ²⁰	83	1237
DRG0903DM00001S	90,000	3,000	180,000	12.2 / 16	208/230-3	93¾	60¾	54¾ ²⁰	83	1247
DRG0903DH00001S	90,000	3,000	225,000	12.2 / 16	208/230-3	93¾	60¾	54¾ ²⁰	83	1256
DRG0904DL00001S	90,000	3,000	130,000	12.2 / 16	460-3	93¾	60¾	54¾ ²⁰	83	1237
DRG0904DM00001S	90,000	3,000	180,000	12.2 / 16	460-3	93¾	60¾	54¾ ²⁰	83	1247
DRG0904DH00001S	90,000	3,000	225,000	12.2 / 16	460-3	93¾	60¾	54¾ ²⁰	83	1256
DRG0907DL00001S	90,000	3,000	130,000	12.2 / 16	575-3	93¾	60¾	54¾ ²⁰	83	1237
DRG0907DM00001S	90,000	3,000	180,000	12.2 / 16	575-3	93¾	60¾	54¾ ²⁰	83	1247
DRG0907DH00001S	90,000	3,000	225,000	12.2 / 16	575-3	93¾	60¾	54¾ ²⁰	83	1256
DRG1023DL00001S	102,000	3,100	130,000	12.2/17	208/230-3	93¾	60¾	54¾ ²⁰	80	1248
DRG1023DM00001S	102,000	3,100	180,000	12.2/17	208/230-3	93¾	60¾	54¾ ²⁰	80	1258
DRG1023DH00001S	102,000	3,100	225,000	12.2/17	208/230-3	93¾	60¾	54¾ ²⁰	80	1267
DRG1024DL00001S	102,000	3,100	130,000	12.2/17	460-3	93¾	60¾	54¾ ²⁰	80	1248
DRG1024DM00001S	102,000	3,100	180,000	12.2/17	460-3	93¾	60¾	54¾ ²⁰	80	1258
DRG1024DH00001S	102,000	3,100	225,000	12.2/17	460-3	93¾	60¾	54¾ ²⁰	80	1267
DRG1027DL00001S	102,000	3,100	130,000	12.2/17	575-3	93¾	60¾	54¾ ²⁰	80	1248
DRG1027DM00001S	102,000	3,100	180,000	12.2/17	575-3	93¾	60¾	54¾ ²⁰	80	1258
DRG1027DH00001S	102,000	3,100	225,000	12.2/17	575-3	93¾	60¾	54¾ ²⁰	80	1267

¹ BTU/h | Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.

LIGHT COMMERCIAL

DRG – High-Efficiency Gas/Electric Direct-Drive 7½ to 12½ Tons (cont.)



*Complete warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

Model	Nominal Capacities ¹			EER / IEER	Voltage-Phase	Dimensions			Sound Level dB(A)	Ship Weight (lbs)
	Cooling	CFM	Heating			W"	D"	H"		
DRG1203DL00001S	115,000	3,550	130,000	12.2/17	208/230-3	93¾	60⅝	54⅞ ₂₀	82	1267
DRG1203DM00001S	115,000	3,550	180,000	12.2/17	208/230-3	93¾	60⅝	54⅞ ₂₀	82	1277
DRG1203DH00001S	115,000	3,550	240,000	12.2/17	208/230-3	93¾	60⅝	54⅞ ₂₀	82	1290
DRG1204DL00001S	115,000	3,550	130,000	12.2/17	460-3	93¾	60⅝	54⅞ ₂₀	82	1267
DRG1204DM00001S	115,000	3,550	180,000	12.2/17	460-3	93¾	60⅝	54⅞ ₂₀	82	1277
DRG1204DH00001S	115,000	3,550	240,000	12.2/17	460-3	93¾	60⅝	54⅞ ₂₀	82	1290
DRG1207DL00001S	115,000	3,550	130,000	12.2/17	575-3	93¾	60⅝	54⅞ ₂₀	82	1267
DRG1207DM00001S	115,000	3,550	180,000	12.2/17	575-3	93¾	60⅝	54⅞ ₂₀	82	1277
DRG1207DH00001S	115,000	3,550	240,000	12.2/17	575-3	93¾	60⅝	54⅞ ₂₀	82	1290
DRG1503DL00001S	137,000	3,800	130,000	11.5/15.5	208/230-3	93¾	60⅝	58⅝	81	1345
DRG1503DM00001S	137,000	3,800	180,000	11.5/15.5	208/230-3	93¾	60⅝	58⅝	81	1355
DRG1503DH00001S	137,000	3,800	240,000	11.5/15.5	208/230-3	93¾	60⅝	58⅝	81	1368
DRG1504DL00001S	137,000	3,800	130,000	11.5/15.5	460-3	93¾	60⅝	58⅝	81	1345
DRG1504DM00001S	137,000	3,800	180,000	11.5/15.5	460-3	93¾	60⅝	58⅝	81	1355
DRG1504DH00001S	137,000	3,800	240,000	11.5/15.5	460-3	93¾	60⅝	54⅞ ₂₀	81	1368
DRG1507DL00001S	137,000	3,800	130,000	11.5/15.5	575-3	93¾	60⅝	58⅝	81	1345
DRG1507DM00001S	137,000	3,800	180,000	11.5/15.5	575-3	93¾	60⅝	58⅝	81	1355
DRG1507DH00001S	137,000	3,800	240,000	11.5/15.5	575-3	93¾	60⅝	58⅝	81	1368

¹ BTU/h | Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.



*Complete warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

DP14CM – Three-Phase Packaged Air Conditioners 3 to 5 Tons



The Daikin DP14CM Commercial Packaged Air Conditioner provides energy-efficient cooling and cooling performance in one self-contained unit. This unit uses the chlorine-free refrigerant R-410A. The DP14CM is housed in a heavy-gauge, galvanized-steel cabinet that offers a high-quality, UV-resistant powder-paint finish and allows for a ground-level or rooftop mount.

DESIGNED FOR EXCEPTIONAL DURABILITY, ENERGY EFFICIENCY, AND OUTSTANDING PERFORMANCE.

- | | | |
|--|---|--|
| <ul style="list-style-type: none"> » Energy-efficient compressor with internal relief valve » Fully charged R-410A system » EEM blower motor; PSC blower motor on 3-ton units » Copper tube/aluminum fin coils | <ul style="list-style-type: none"> » Totally enclosed, permanently lubricated condenser fan motor » Electric heat kit available as a field-installed option » Convertible airflow — horizontal or downflow | <ul style="list-style-type: none"> » Louvered condenser coil protection » Heavy-gauge galvanized-steel cabinet with attractive nickel gray powder-paint finish » Fully insulated air-handling compartment with convenient access panels |
|--|---|--|

Model	Nominal Ratings		SEER / EER	Voltage-Phase	Dimensions			dB(A)	Ship Weight (lbs)
	Cooling ¹	CFM			W"	D"	H"		
DP14CM3643A*	35,000	1,200	14.0 / 11.0	208/230-3	47	51	34¾	80.1	365
DP14CM4843A*	45,500	1,600	14.0 / 11.0	208/230-3	47	51	42¾	81.7	435
DP14CM6043A*	56,000	1,700	14.0 / 11.0	208/230-3	47	51	42¾	80.2	458

¹Tons | Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.

DP14HM – Three-Phase Packaged Heat Pumps 3 to 5 Tons



*Complete warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

The Daikin DP14HM Commercial Packaged Heat Pump provides energy-efficient cooling and heating performance in one self-contained unit. This unit uses the chlorine-free refrigerant R-410A. This unit is housed in a heavy-gauge, galvanized-steel cabinet that offers a high-quality, UV-resistant powder-paint finish and allows for a ground-level or rooftop mount.



DESIGNED FOR EXCEPTIONAL DURABILITY, ENERGY EFFICIENCY, AND OUTSTANDING PERFORMANCE.

- » Energy-efficient compressor with internal relief valve
- » Fully charged with R-410A chlorine-free refrigerant
- » EEM blower motor
- » Copper tube/aluminum fin coil
- » Convertible airflow — horizontal or downflow
- » Totally enclosed, permanently lubricated condenser fan motor
- » Electric heat kit available as a field-installed accessory
- » Heavy-gauge galvanized-steel cabinet
- » Attractive nickel gray powder-paint finish
- » Fully insulated blower compartment with convenient access panels
- » Louvered condenser coil protection
- » One footprint; two heights

Model	Nominal Capacities				SEER / EER	COP-47F	COP-17F	HSPF	Voltage-Phase	Dimensions			dB(A)	Ship Weight (lbs)
	Cooling ¹	CFM	Heating CAP 47F btu/hr	Heating CAP 17F btu/hr						W"	D"	H"		
DP14HM3643A*	34,400	1,200	33,200	19,000	14.0 / 11.0	3.6	2.2	8	208/230-3	47	51	34¾	81	400
DP14HM4843A*	48,000	1,600	45,500	26,600	14.0 / 11.0	3.6	2.2	8	208/230-3	47	51	42¾	79	475
DP14HM6043A*	58,000	1,850	57,000	31,400	14.0 / 11.0	3.5	2.2	8	208/230-3	47	51	42¾	80	495

¹Tons, ² BTU/h | Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.



*Complete warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

DP14GM / UM – Three-Phase Packaged Gas/Electric 3 to 5 Tons



The Daikin DP14GM Commercial Packaged Gas/Electric Units feature the chlorine-free refrigerant R-410A. Other features include our corrosion-resistant tubular heat exchanger and an energy-efficient scroll compressor. These units are housed in a heavy-gauge, galvanized-steel cabinet with UV-resistant powder-paint finish.

DESIGNED FOR EXCEPTIONAL DURABILITY, ENERGY EFFICIENCY, AND OUTSTANDING PERFORMANCE.

- » Energy-efficient compressor with internal relief valve
- » EEM blower motor; PSC blower motor on 3-ton units
- » Durable, corrosion-resistant aluminized-steel tubular heat exchanger
- » Fully charged R-410A system
- » Copper tube/aluminum fin coils
- » Gas valve for natural gas with easy conversion to propane
- » Direct-spark ignition system includes a microprocessor-based control for the entire ignition sequence
- » All blower operation and all safety circuits complete with self-diagnostics
- » All models comply with California Low NO_x standards
- » AHRI Certified; ETL Certified
- » Heavy-gauge, galvanized-steel cabinet with UV-resistant powder-paint finish
- » Fully insulated cabinet
- » One roof curb fits all units
- » One footprint; one height
- » Convenient access panels
- » Fits in a standard-size pick-up truck
- » For installation in California's South Coast Air Quality Management District (SCAQMD) only: This furnace does not meet the SCAQMD Rule 1111 14 ng/J NO_x emission limit, and thus is subject to a mitigation fee of up to \$450. This furnace is not eligible for the SCAQMD Clean Air Furnace Rebate Program: www.CleanAirFurnaceRebate.com.

Model	Nominal Capacities			SEER / EER	Voltage-Phase	Dimensions			dB(A)	Ship Weight (lbs)
	Cooling ¹	CFM	Heating ²			W"	D"	H"		
DP14GM3608043A*	35,000	1,200	80,000	14.0 / 11.0	208/230-3	47	51	34¾	78	480
DP14GM4808043A*	46,000	1,525	80,000	14.0 / 11.0	208/230-3	47	51	42¾	80	545
DP14GM6108043A*	56,500	1,750	80,000	14.0 / 11.0	208/230-3	47	51	42¾	80	555
DP14GM6112043A*	56,500	1,750	120,000	14.0 / 11.0	208/230-3	47	51	42¾	80	565
ULN Models										
DP14UM3608043C*	34,200	1,200	80,000	14.0 / 11.0	208/230-3	47	51	34¾	78	520
DP14UM4808043C*	46,500	1,525	80,000	14.0 / 11.0	208/230-3	47	51	42¾	80	555
DP14UM6108043C*	56,500	1,750	80,000	14.0 / 11.0	208/230-3	47	51	42¾	78	555

¹Tons, ² BTU/h | Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.

DX3SEA – 13.2 SEER2

Air Conditioners

3 to 5 Tons



*Complete warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

The Daikin DX3SEA Three-Phase Air Conditioner uses the chlorine-free refrigerant R-410A and features operating sound levels that are among the best in the heating and cooling industry. With its minimum of 13.2 SEER2 rating, the DX3SEA will help reduce energy consumption throughout the life of the system compared to lower SEER2 rated equipment.



DESIGNED FOR EXCEPTIONAL DURABILITY, ENERGY EFFICIENCY, AND OUTSTANDING PERFORMANCE.

- | | | |
|---|--|--|
| <ul style="list-style-type: none"> » R-410A chlorine-free refrigerant » Energy-efficient compressor » Factory-installed filter drier » Copper tube/enhanced aluminum fin coil » Complies with ASHRAE Standard 90.1 | <ul style="list-style-type: none"> » AHRI Certified; ETL Listed » Louvered sound control top design » Steel louver coil guard » Heavy-gauge galvanized-steel cabinet | <ul style="list-style-type: none"> » Attractive nickel gray powder-paint finish » Top and side maintenance access » Single-panel access to controls with space provided for field-installed accessories |
|---|--|--|

Model	Cooling Capacity (BTU/h)	Voltage-Phase Phase	Dimensions			Service Valve		Sound Level dB(A)	Ship Weight (lbs)
			W"	D"	H"	Liquid"	Suction"		
DX3SEA3630	36,000	200/230-3	29"	29"	32½"	¾"	¾"	73	163
DX3SEA3640	36,000	460-3	29"	29"	32½"	¾"	¾"	73	164
DX3SEA4830	48,000	200/230-3	35½"	35½"	35¾"	¾"	¾"	74	231
DX3SEA4840	48,000	460-3	35½"	35½"	35¾"	¾"	¾"	74	231
DX3SEA6030	60,000	200/230-3	35½"	35½"	39½"	¾"	¾"	75	240
DX3SEA6040	60,000	460-3	35½"	35½"	39½"	¾"	¾"	75	240

Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.



*Complete warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

DX14XA - 11.2 EER / 15.2 IEER

Air Conditioners 7½ & 10 Tons



The Daikin DX14XA Commercial Air Conditioner cabinet features a powder-paint finish over heavy-gauge galvanized steel that provides premium durability and improved UV protection. Designed for ground-level or rooftop mount, the base pan elevates the unit above the slab to provide excellent water drainage and keep the coil away from debris that can collect inside the unit. The unit's attractive louvered metal guard protects the coil from damage and strengthens the unit.

DESIGNED FOR EXCEPTIONAL DURABILITY, ENERGY EFFICIENCY, AND OUTSTANDING PERFORMANCE.

- | | | |
|---|--|---|
| <ul style="list-style-type: none"> » R-410A chlorine-free refrigerant » Two-stage energy-efficient compressor with internal relief valve » High-capacity, steel-cased filter drier | <ul style="list-style-type: none"> » High-efficiency copper tube/aluminum fin coil High- and low-pressure switches » AHRI Certified; ETL Listed » Louvered sound control top design | <ul style="list-style-type: none"> » Steel louver coil guard protects coil from damage and adds strength to the unit » Bottom pan rails elevate unit above slab » Heavy-gauge galvanized-steel cabinet » Attractive nickel gray powder-paint finish |
|---|--|---|

Model	Cooling Capacity (BTU/h)	EER / IEER	Voltage-Phase	Dimensions			Service Valve		dB(A)	Ship Weight (lbs)
				W"	D"	H"	Liquid"	Suction"		
DX14XA0903A	90,000	11.2 / 15.2	208/230-3	35½"	35½"	41½"	5⁄8"	1¾"	83.7	325
DX14XA0904A	90,000	11.2 / 15.2	460-3	35½"	35½"	41½"	5⁄8"	1¾"	83.7	325
DX14XA1203A	115,000	11.2 / 15.2	208/230-3	35½"	35½"	41½"	5⁄8"	1¾"	84.7	345
DX14XA1204A	115,000	11.2 / 15.2	460-3	35½"	35½"	41½"	5⁄8"	1¾"	84.7	340

Daikin North America LLC, reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.

DZ4SEA – 14.3 SEER2

Heat Pumps 3 to 5 Tons



*Complete warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

The Daikin Commercial Heat Pump cabinet features a powder-paint finish over heavy-gauge galvanized steel that provides premium durability and improved UV protection. Designed for ground-level or rooftop mount, the base pan elevates the unit above the slab to provide excellent water drainage and keep the coil away from debris that can collect inside the heat pump. The unit's attractive louvered metal guard protects the coil from damage and strengthens the unit.



DESIGNED FOR EXCEPTIONAL DURABILITY, ENERGY EFFICIENCY, AND OUTSTANDING PERFORMANCE.

- | | | |
|--|---|--|
| <ul style="list-style-type: none"> » R-410A chlorine-free refrigerant » Energy-efficient scroll compressor » Low-pressure switch » Liquid refrigerant return protection » Factory-installed, bi-flow liquid line filter drier » Copper tube/enhanced aluminum fin coil | <ul style="list-style-type: none"> » Reliable time-initiated, temperature-terminated defrost control » Contactor with lug connection » Ground lug connection » AHRI Certified; ETL Listed » Louvered sound control top design » Steel louver coil guard | <ul style="list-style-type: none"> » Heavy-gauge galvanized-steel cabinet » Attractive nickel gray powder-paint finish » Top and side maintenance access » Service ports and controls are accessible while unit is operating |
|--|---|--|

Model	Cooling Capacities (BTU/h)		Voltage-Phase	Dimensions			Service Valve		Sound Level dB(A)	Ship Weight (lbs)
	Cooling	Heating		W"	D"	H"	Liquid"	Suction"		
DZ4SEA3630	36,000	36,000	200/230-3	35½"	35½"	39 10/16"	¾"	¾"	74	233
DZ4SEA3640	36,000	36,000	460-3	35½"	35½"	39 10/16"	¾"	¾"	74	236
DZ4SEA4830	48,000	48,000	200/230-3	35½"	35½"	36 7/16"	¾"	¾"	75	292
DZ4SEA4840	48,000	48,000	460-3	35½"	35½"	36 7/16"	¾"	¾"	75	295
DZ4SEA6030	60,000	60,000	200/230-3	35½"	35½"	41 10/16"	¾"	¾"	76	321
DZ4SEA6040	60,000	60,000	460-3	35½"	35½"	41 10/16"	¾"	¾"	76	321

Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.



*Complete warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

DZ14XA - 11 EER / 14.5 IEER

Heat Pumps 7½ & 10 Tons



The Daikin DZ14XA Commercial Heat Pump cabinet features a powder-paint finish over heavy-gauge galvanized steel that provides premium durability and improved UV protection. Designed for ground-level or rooftop mount, the base pan elevates the unit above the slab to provide excellent water drainage and keep the coil away from debris that can collect inside the unit. The unit's attractive louvered metal guard protects the coil from damage and strengthens the unit.

DESIGNED FOR EXCEPTIONAL DURABILITY, ENERGY EFFICIENCY, AND OUTSTANDING PERFORMANCE.

- | | | |
|--|--|--|
| <ul style="list-style-type: none"> » R-410A chlorine-free refrigerant » Two-stage energy-efficient compressor with internal relief valve » High-capacity, steel-cased, bi-flow heat pump filter drier » Discharge line muffler » Liquid refrigerant return protection | <ul style="list-style-type: none"> » Check flowrate heating mode expansion device » Low-pressure switch » Reliable, time-initiated, temperature-terminated defrost control » Brass liquid and suction line service valves » High-efficiency copper tube/aluminum fin coil | <ul style="list-style-type: none"> » AHRI Certified; ETL Listed » Louvered sound control top design » Heavy-gauge galvanized-steel cabinet » Steel louver coil guard protects coil from damage and adds strength to the unit » Attractive nickel gray powder-paint finish |
|--|--|--|

Model	Cooling Capacities (BTU/h)			COP (47F)	COP (17F)	EER / IEER	Voltage-Phase	Dimensions			Service Valve		dB(A)	Ship Weight (lbs)
	Cooling	Heating CAP 47F btu/hr	Heating CAP 17F btu/hr					W"	D"	H"	Liquid"	Suction"		
DZ14XA0903A	90,000	78,000	50,000	3.4	2.25	11 / 14.5	208/230	35½	35½	41½	⅝"	1⅞"	83.3/85.3	355
DZ14XA0904A	90,000	78,000	50,000	3.4	2.25	11 / 14.5	460	35½	35½	41½	⅝"	1⅞"	83.3/85.4	355
DZ14XA1203A	115,000	97,000	60,000	3.4	2.25	11 / 14.5	208/230	35½	35½	41½	⅝"	1⅞"	85.1/86.1	375
DZ14XA1204A	115,000	97,000	60,000	3.4	2.25	11 / 14.5	460	35½	35½	41½	⅝"	1⅞"	85.1/86.1	370

Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.

DAX – Multi-Speed Upflow Air Handler 7½ & 10 Tons



*Complete warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

The Daikin DAX Multi-Speed, Multi-Position Air Handlers are suitable for upflow or left side horizontal installations to accompany your 7½ and 10-ton split-system units. These unit feature a fully insulated fiberglass blanket for quiet, efficient operation.



DESIGNED FOR EXCEPTIONAL DURABILITY, ENERGY EFFICIENCY, AND OUTSTANDING PERFORMANCE.

- » Circuited for use with one (1) 7½-ton or one (1) 10-ton cooling-only or heat pump system.
- » Copper tube/aluminum fin coils
- » TXV control; 7½-ton unit has one (2) thermal expansion valves; 10-ton unit has two (2) thermal expansion valves
- » Draw-thru centrifugal blower is direct-driven for quiet, efficient operation
- » Heavy-gauge, reinforced, galvanized-steel cabinet
- » Fully insulated with fiberglass blanket
- » Horizontal and vertical condensate pans
- » Built-in filter rack (2" filter included)
- » Entry on top of panel for both low and high voltages
- » Removable access panels make servicing of unit faster and easier

Model	Nominal Cooling (BTU/h)	Electric Heat (kW)	CFM @ 0.3" ESP	Voltage-Phase Phase	Dimensions			Service Valve		Ship Weight (lbs)
					W"	D"	H"	Liquid"	Suction"	
DAX09043	90,000	15, 20, 30	3,000	208/240-3	48½	24	60½	¾"	1½"	430
DAX09044	90,000	15, 20, 30	3,000	460-3	48½	24	60½	¾"	1½"	430
DAX12043	120,000	15, 20, 30	4,000	208/240-3	48½	24	60½	¾"	1½"	430
DAX12044	120,000	15, 20, 30	4,000	460-3	48½	24	60½	¾"	1½"	430

*For two refrigerant lines

Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.