



Unitary Packaged Units



COMFORTABLE LIMITED WARRANTY* PROTECTION

* Complete warranty details available from your local dealer/contractor or at www.daikincomfort.com. To receive the 12-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. The duration of warranty coverage in Texas and Florida differs in some cases.

Additional requirements for annual maintenance are required for the Unit Replacement Limited Warranty. Online registration and some of the additional requirements are not required in California or Québec.

Standard Features

- » Energy-efficient compressor with internal relief valve
- » Multi-Speed ECM indoor blower motor
- » Quiet horizontal discharge
- » All-aluminum evaporator coil
- » Copper tube / aluminum fin condenser coil
- » Totally enclosed, permanently lubricated condenser fan motor
- » Fully charged R-410A system
- » 5 kW to 20 kW electric heat kit available as a field-installed option
- » Heavy-gauge galvanized-steel cabinet with attractive Nickel Gray powder-paint finish
- » Compressor sound blanket
- » One foot print; 2 heights
- » Aluminum foil-facing internal insulation reinforced with fiberglass scrim
- » Meets cabinet air leakage requirements when tested in accordance with ASHRAE standard 193
- » Fully insulated blower compartment with convenient access panels
- » Louvered condenser coil protection
- » When properly anchored, meets the 2020 Florida Building Code unit integrity requirements for hurricane-type winds (Anchor bracket kits available.)
- » AHRI Certified; ETL listed

The DP3CH packaged home air conditioner is designed for horizontal installation. It comes with an energy-efficient scroll compressor that delivers dependable cooling for lower energy bills compared to lower SEER2 units. Plus, you will be happy to know that your Daikin system uses chlorine-free R-410A refrigerant. Our packaged air conditioner units are also furnished with a variable-speed ECM blower motor that offers silent system startup and shutdown with extremely efficient performance. The heavy-gauge galvanized steel enclosure with a powder-coat finish will shield your system from extreme weather. Supports 2023 DOE Energy Efficiency Standards



**20
23**
SEER2

Model	Cooling Capacity		SEER2/ EER2	Electric Heat (kW)	Voltage- Phase	MCA	MOP	Dimensions			Ship Weight (lbs)	
	BTU/h	CFM						W"	D"	H"		
DP3CH2441*	24,000	875	13.4 / 10.6	5, 8, 10	208/230-1	14.5	20	66	34	22	76	324
DP3CH3041*	30,000	1,050	13.4 / 10.6	5, 8, 10, 15	208/230-1	21.6	35	66	34	22	76	324
DP3CH3641*	36,000	1,200	13.4 / 10.6	5, 8, 10, 15	208/230-1	24.4	35	66	34	22	78	387
DP3CH4241*	42,000	1,200	13.4 / 10.6	5, 8, 10, 15, 20	208/230-1	29.2	45	66	34	22	78	387
DP3CH4841*	48,000	1,600	13.4 / 10.6	5, 8, 10, 15, 20	208/230-1	31.7	50	66	34	24	80	387
DP3CH6041*	60,000	1,600	13.4 / 10.6	5, 8, 10, 15, 20	208/230-1	35.4	50	66	34	24	80	412

The manufacturing entity reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.

COMFORTABLE LIMITED WARRANTY* PROTECTION



* Complete warranty details available from your local dealer/contractor or at www.daikincomfort.com. To receive 6-Year Unit Replacement Limited Warranty and 12-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. The duration of warranty coverage in Texas and Florida differs in some cases.

Additional requirements for annual maintenance are required for the Unit Replacement Limited Warranty. Online registration and some of the additional requirements are not required in California or Québec.

DP5HH

Packaged Heat Pumps

Up to 15.2 SEER2

Standard Features

- » High-efficiency scroll compressor
- » Variable-speed ECM blower motor
- » Quiet horizontal discharge
- » All-aluminum evaporator coil
- » Copper tube/aluminum fin coil
- » Totally enclosed, permanently lubricated condenser fan motor
- » Fully charged system
- » Electric heat kit available as a field-installed option
- » AHRI Certified; ETL Listed
- » Heavy-gauge galvanized-steel cabinet
- » UV-resistant grey powder-paint finish
- » Compressor sound blanket
- » Aluminum foil-facing internal insulation reinforced with fiberglass scrim
- » Meets cabinet air leakage requirements when tested in accordance with ASHRAE standard 193
- » Attractive Nickel Gray powder-paint finish
- » Fully insulated blower compartment has convenient access panels
- » Louvered condenser coil protection
- » One footprint; three heights
- » When properly anchored, meets the 2020 Florida Building Code unit integrity requirements for hurricane-type winds (Anchor bracket kits available.)

The DP5HH packaged heat pump has a high-efficiency scroll compressor that provides optimal performance. Two-stage* heating and cooling, a variable-speed ECM blower motor, and an all-aluminum evaporator coil are only a few of the features that come stock with this 15.2 SEER2 heat pump system. The heavy-gauged galvanized-steel cabinet with nice-looking nickel gray powder-paint finish makes this unit very attractive. Supports 2023 DOE Energy Efficiency Standards.

*Model specific, please refer to product specifications for more information.



**20
23**
SEER2

UNITARY PRODUCTS

Model	Nominal Ratings			Electric Heat (kW)	SEER2/ EER2	Voltage-Phase	MCA	MOP	Dimensions			dBs	Ship Weight (lbs)
	Cooling (BTU/h)	Heating (BTU/h)	Cooling (CFM)						W"	D"	H"		
DP5HH2441**	24,000	24,000	875	5, 8, 10	15.0 / 11.4	208/230-1	21.3	30	66	34	30	76	324
DP5HH3041**	30,000	30,000	1,050	5, 8, 10, 15	15.2 / 11.4	208/230-1	22.9	35	66	34	30	76	324
DP5HH3641**	36,000	36,000	1,200	5, 8, 10, 15	15.2 / 11.4	208/230-1	23.2	35	66	34	35	78	385
DP5HH4241*	42,000	42,000	1,300	5, 8, 10, 15, 20	15.2 / 11.4	208/230-1	30.6	50	66	34	35	79	385
DP5HH4841**	48,000	48,000	1,600	5, 8, 10, 15, 20	15.2 / 11.2	208/230-1	34.7	50	66	34	35	78	415
DP5HH6041**	60,000	60,000	1,700	5, 8, 10, 15, 20	15.2 / 11.4	208/230-1	40.2	60	66	34	38.5	80	415

The manufacturing entity reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.

Packaged Heat Pump

15.2 SEER2 / 6.8 HSPF



COMFORTABLE LIMITED WARRANTY* PROTECTION

* Complete warranty details available from your local dealer/contractor or at www.daikincomfort.com. To receive 6-Year Unit Replacement Limited Warranty and 12-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. The duration of warranty coverage in Texas and Florida differs in some cases.

Additional requirements for annual maintenance are required for the Unit Replacement Limited Warranty. Online registration and some of the additional requirements are not required in California or Québec.

Standard Features

- » Two-stage heating & cooling
- » Energy-efficient two-stage scroll compressor with internal relief valve
- » Multi-speed ECM indoor blower motor
- » Liquid-line filter drier
- » Convertible airflow: horizontal or downflow
- » Copper tube/aluminum fin condenser coils
- » Compressor sound blanket
- » Heavy-gauge galvanized-steel cabinet with attractive two-tone Architectural Gray powder-paint finish
- » Aluminum foil-facing internal insulation reinforced with fiberglass scrim
- » Fully insulated air-handling compartment with convenient access panels
- » Louvered condenser coil protection
- » All-aluminum evaporator coil on 2- to 4-ton units
- » Copper Tube/ Aluminum Fin Evaporator coil (5 Ton)
- » Totally enclosed, permanently lubricated condenser fan motor
- » Electric heat kit available as a field-installed option
- » Compressor grommets for vibration isolation
- » Convenient access panels
- » Compressor sound blanket
- » Bottom, 2" high base rails for easier handling
- » Louvered condenser coil protection
- » When properly anchored, meets the 2020 Florida Building Code unit integrity requirements for hurricane-type winds (Anchor bracket kits available.)
- » AHRI Certified; ETL Listed

The DP5HM packaged heat pump has an energy-efficient compressor that provides optimum performance. Two-stage* heating and cooling, a variable-speed ECM blower motor, and an aluminum evaporator coil are just a few features that come standard with this 15.2 SEER2 heat pump system. The fully insulated heavy-gauge, zinc-coated steel cabinet with UV-resistant grey powder-paint finish (Sandstone Beige for the 5-ton model) makes this unit very attractive. Supports 2023 DOE Energy Efficiency Standards.

* Model specific, please refer to product specifications for more information.



**20
23
SEER2**

Model	Nominal Ratings			Electric Heat (kW)	SEER2/EER2	Voltage-Phase	MCA	MOP	Dimensions			dBs	Ship Weight (lbs)
	Cooling (BTU/h)	Heating (BTU/h)	Cooling (CFM)						W"	D"	H"		
DP5HM2441A*	24,000	24,000	850	5, 8, 10	15.2 / 11.4	208 / 230-1	19.2	30	47	51	34½	76	376
DP5HM3041A*	30,000	30,000	1050	5, 8, 10, 15	15.2 / 11.4	208 / 230-1	22	35	47	51	34½	76	385
DP5HM3641A*	36,000	36,000	1200	5, 8, 10, 15	15.2 / 11.4	208 / 230-1	23.3	35	47	51	42¾	81	492
DP5HM4241A*	42,000	42,000	1300	5, 8, 10, 15, 20	15.2 / 11.4	208 / 230-1	33.1	50	47	51	42¾	80	492
DP5HM4841A*	48,000	48,000	1600	5, 8, 10, 15, 20	15.2 / 11.2	208 / 230-1	34.7	50	47	51	42¾	79	492
DP5HM6041A*	60,000	60,000	2000	5, 8, 10, 15, 20	15.2 / 11.2	208 / 230-1	39	60	73 3/8	47 5/8	43½	80	688

The manufacturing entity reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.

COMFORTABLE LIMITED
WARRANTY* PROTECTION



* Complete warranty details available from your local dealer/contractor or at www.daikincomfort.com. To receive the 12-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. The duration of warranty coverage in Texas and Florida differs in some cases.

Additional requirements for annual maintenance are required for the Unit Replacement Limited Warranty. Online registration and some of the additional requirements are not required in California or Québec.

DP3HH

Packaged Heat Pump

13.4 SEER2 / 6.70 HSPF2

Standard Features

- » Energy-efficient compressor with internal relief valve
- » Multi-speed ECM indoor blower motor
- » Quiet horizontal discharge
- » Copper tube/corrosion-resistant fin
- » Totally enclosed, permanently lubricated condenser fan motor
- » Fully charged system
- » Electric heat kit available as a field-installed option
- » Compressor sound blanket
- » AHRI Certified; ETL listed
- » Heavy-gauge galvanized-steel cabinet with attractive Nickel Gray powder-paint finish
- » Aluminum foil-facing internal insulation reinforced with fiberglass scrim
- » Meets cabinet air leakage requirements when tested in accordance with ASHRAE standard 193
- » Fully insulated blower compartment has convenient access panels
- » Louvered condenser coil protection
- » One footprint; three heights
- » When properly anchored, meets the 2020 Florida Building Code unit integrity requirements for hurricane-type winds (Anchor bracket kits available.)

The Daikin brand DP3HH Energy-Efficient Packaged Heat Pump features energy-efficient cooling and heating performance in one self-contained unit. This unit is housed in a heavy-gauge, galvanized-steel cabinet protected by a high-quality, UV-resistant powder-paint finish. The DP3HH allows for ground-level or rooftop applications. Supports 2023 DOE Energy Efficiency Standards



**20
23**
SEER2

UNITARY PRODUCTS

Model	Nominal Ratings			Electric Heat (kW)	SEER2 / EER	Voltage-Phase	MCA	MOP	Dimensions			dBs	Ship Weight (lbs)
	Cooling (BTU/h)	Heating (BTU/h)	Cooling (CFM)						W"	D"	H"		
DP3HH2441*	24,000	24,000	875	5, 8, 10	13.4 / 10.6	208/230-1	20.8	30	66	34	30	76	324
DP3HH3041*	30,000	30,000	1,050	5, 8, 10, 15	13.4 / 10.6	208/230-1	22.4	35	66	34	30	76	324
DP3HH3641*	36,000	36,000	1,200	5, 8, 10, 15	13.4 / 10.6	208/230-1	26	40	66	34	35	78	387
DP3HH4241*	42,000	42,000	1,300	5, 8, 10, 15, 20	13.4 / 10.6	208/230-1	26.1	40	66	34	35	78	387
DP3HH4841*	48,000	48,000	1,570	5, 8, 10, 15, 20	13.4 / 10.6	208/230-1	31.7	50	66	34	35	80	387
DP3HH6041*	60,000	60,000	1,700	5, 8, 10, 15, 20	13.4 / 10.6	208/230-1	39.8	60	66	34	38½	80	412

The manufacturing entity reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.

Packaged Heat Pump

13.4 SEER2 / 6.7 HSPF2



COMFORTABLE LIMITED WARRANTY* PROTECTION

* Complete warranty details available from your local dealer/contractor or at www.daikincomfort.com. To receive the 12-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. The duration of warranty coverage in Texas and Florida differs in some cases.

Additional requirements for annual maintenance are required for the Unit Replacement Limited Warranty. Online registration and some of the additional requirements are not required in California or Québec.

Standard Features

- » Energy-efficient compressor with internal relief valve
- » Two-stage cooling on 5-ton units
- » All-aluminum evaporator coil
- » Multi-Speed ECM indoor blower motor
- » Liquid-line filter drier
- » Convertible airflow: horizontal or downflow
- » Copper tube/aluminum fin condenser coils
- » Totally enclosed, permanently lubricated condenser fan motor
- » Electric heat kit available as a field-installed option
- » Heavy-gauge galvanized-steel cabinet with attractive UV-resistant powder-paint finish
- » Fully insulated air-handling compartment with convenient access panels
- » Aluminum foil-facing internal insulation reinforced with fiberglass scrim
- » Compressor sound blanket
- » Louvered condenser coil protection
- » One footprint; two heights
- » AHRI Certified; ETL Listed
- » When properly anchored, meets the 2020 Florida Building Code unit integrity requirements for hurricane-type winds (Anchor bracket kits available.)

The DP3HM packaged heat pump has an energy-efficient compressor that provides optimum performance. single-stage heating and cooling, a multi-speed ECM blower motor, and an aluminum evaporator coil are just a few features that come standard with this 13.4 SEER2 heat pump system. The fully insulated heavy-gauge, zinc-coated steel cabinet with UV-resistant grey powder-paint finish makes this unit very attractive. Supports 2023 DOE Energy Efficiency Standards.



**20
23**
SEER2

Model	Nominal Ratings			Electric Heat (kW)	SEER2 / EER2	Voltage-Phase	MCA	MOP	Dimensions			dBs	Ship Weight (lbs)
	Cooling (BTU/h)	Heating (BTU/h)	Cooling (CFM)						W"	D"	H"		
DP3HM2441**	24,000	24,000	850	5, 8, 10	13.4 / 10.6	208/230-1	21.4	30	47	51	34 $\frac{1}{4}$	76	380
DP3HM3041**	30,000	30,000	1,050	5, 8, 10, 15	13.4 / 10.6	208/230-1	23	35	47	51	34 $\frac{1}{4}$	76	390
DP3HM3641**	36,000	36,000	1,200	5, 8, 10, 15	13.4 / 10.6	208/230-1	24.4	35	47	51	42 $\frac{3}{4}$	81	400
DP14HM4241**	48,000	48,000	1,300	5, 8, 10, 15	13.4 / 10.6	208/230-1	29.2	45	47	51	42 $\frac{3}{4}$	80	485
DP14HM4841**	60,000	60,000	1,600	5, 8, 10, 15, 20	13.4 / 10.6	208/230-1	31.9	50	47	51	42 $\frac{3}{4}$	79	495
DP14HM6041A*	60,000	60,000	1,850	5, 8, 10, 15, 20	13.4 / 10.6	208/230-1	37.5	60	73 $\frac{1}{8}$	47 $\frac{1}{8}$	43 $\frac{1}{2}$	80	495

¹Tons

The manufacturing entity reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.

COMFORTABLE LIMITED WARRANTY* PROTECTION



* Complete warranty details available from your local dealer/contractor or at www.daikincomfort.com. To receive the Lifetime Heat Exchanger Limited Warranty (good for as long as you own your home), 6-Year Unit Replacement Limited Warranty and 12-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. The duration of warranty coverage in Texas and Florida differs in some cases.

Additional requirements for annual maintenance are required for the Unit Replacement Limited Warranty. Online registration and some of the additional requirements are not required in California or Québec.

DP5GM

Packaged Gas & Electric

Up to 15.2 SEER2 / 8.0 HSPF

Standard Features

- » Heavy-duty stainless-steel heat exchanger
- » High-efficiency two-stage scroll compressor with factory-installed sound blanket
- » Multi-speed ECM indoor blower motor
- » Copper tube/aluminum fin evaporator coil (5 Ton)
- » All-aluminum evaporator coil (2-4 Ton)
- » Two-stage gas valve; natural gas with easy conversion to propane
- » Power-assisted combustion
- » All blower operation and all safety circuits complete with self-diagnostics
- » Loss-of-charge protection and high-pressure switch
- » Direct-spark ignition system with microprocessor-based control for the entire ignition sequence
- » Can not be installed in California's South Coast Air Quality Management District (SCAQMD) and San Joaquin Valley Air Pollution Control District (SJVAPCD).
- » All models comply with California Low NOx standards.
- » AHRI Certified; ETL Listed
- » Fully insulated heavy-gauge, zinc-coated steel cabinet with UV-resistant grey powder-paint finish (Sandstone Beige for the 5-ton model)
- » Aluminum foil-facing internal insulation reinforced with fiberglass scrim
- » Louvered condenser coil protection
- » Compressor sound blanket
- » Compressor grommets for vibration isolation
- » Horizontal or downflow application
- » Convenient access panels
- » Bottom 2" high base rails for easier handling
- » When properly anchored, meets the 2020 Florida Building Code unit integrity requirements for hurricane-type winds (Anchor bracket kits available.)

The DP5GM gas/electric packaged unit has an energy-efficient compressor that provides optimum performance. Two-stage heating and cooling, a variable-speed ECM blower motor, and an aluminum evaporator coil are just a few features that come standard with this 15.2 SEER2 gas/electric packaged unit. The fully insulated heavy-gauge, zinc-coated steel cabinet with UV-resistant grey powder-paint finish (Sandstone Beige for the 5-ton model) makes this unit very attractive. Supports 2023 DOE Energy Efficiency Standards.



5 Tons



2 - 4 Tons

**20
23**
SEER2

Model	Nominal Ratings			SEER2 / EER2	Voltage-Phase	MCA	MOP	Dimensions			DBs	Ship Weight (lbs)
	Cooling ¹	Heating ²	Cooling ³					W"	D"	H"		
DP5GM2406041A*	24,000	60,000	800	15.2 / 11.2	208/230-1	18.4	25	47	51	34½	77	380
DP5GM3008041A*	30,000	80,000	950	14.6 / 11.2	208/230-1	22.0	35	47	51	34½	76	407
DP5GM3608041A*	36,000	80,000	1,200	15.2 / 11.2	208/230-1	25.8	35	47	51	42½	78	480
DP5GM4210041A*	42,000	100,000	1,250	14.7 / 11.2	208/230-1	33.1	50	47	51	42½	79	505
DP5GM4810041A*	48,000	100,000	1,300	15.0 / 11.2	208/230-1	33.7	50	47	51	42½	78	500
DP5GM6014041A*	60,000	140,000	2,000	15.2 / 11.2	208/230-1	43.3	70	73½	47½	43½	78	655

¹ BTU/h ² BTU/h ³ CFM

The manufacturing entity reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.

DP5UM

Packaged Gas & Electric

Up to 15.2 SEER2 / 81% AFUE

COMFORTABLE LIMITED WARRANTY* PROTECTION



* Complete warranty details available from your local dealer/contractor or at www.daikincomfort.com. To receive the Lifetime Heat Exchanger Limited Warranty (good for as long as you own your home), 6-Year Unit Replacement Limited Warranty and 12-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. The duration of warranty coverage in Texas and Florida differs in some cases.

Additional requirements for annual maintenance are required for the Unit Replacement Limited Warranty. Online registration and some of the additional requirements are not required in California or Québec.

Standard Features

- » Heavy-duty stainless-steel heat exchanger
- » High-efficiency two-stage scroll compressor with factory-installed sound blanket
- » Multi-speed ECM indoor blower motor
- » All-aluminum evaporator coil
- » TXV expansion device
- » Single-stage gas valve
- » Power-assisted combustion
- » All blower operation and all safety circuits complete with self-diagnostics
- » Loss-of-charge protection and high-pressure switch
- » Direct-spark ignition system with microprocessor-based control for the entire ignition sequence
- » All Ultra-Low NOx DP5UM models comply with the 14 ng/J emission limit specified in the South Coast Air Quality Management District (SCAQMD) Rule 1111 and San Joaquin Valley Air Pollution Control District (SJVAPCD) Rule 4905. Learn more at www.aqmd.gov and www.valleyair.org.
- » AHRI Certified
- » ETL Listed
- » Fully insulated heavy-gauge, zinc-coated steel cabinet with UV-resistant grey powder-paint finish
- » Aluminum foil-facing internal insulation reinforced with fiberglass scrim
- » Louvered condenser coil protection
- » Compressor sound blanket
- » Compressor grommets for vibration isolation
- » Horizontal or downflow application
- » Convenient access panels
- » Bottom 2" high base rails for easier handling
- » When properly anchored, meets the 2020 Florida Building Code unit integrity requirements for hurricane-type winds (Anchor bracket kits available.)

The DP5UM Ultra-Low NOx gas/electric packaged air conditioner unit has an energy-efficient compressor that provides optimum performance. One-stage heating and two-stage cooling, it comes with factory-installed compressor sound blanket that provides great noise dampening. Heavy-duty stainless-steel heat exchanger, all-aluminum evaporator coil, and multi-speed ECM blower motor are just a few features that come stock with this 15.2 SEER2 gas / electric HVAC unit. The fully insulated heavy-gauge, zinc-coated steel cabinet with UV-resistant grey powder-paint finish makes this unit very attractive. Supports 2023 DOE Energy Efficiency Standards.



**20
23**
SEER2

Model	Nominal Ratings			SEER2 / EER	Voltage-Phase	MCA	MOP	Dimensions			dBs	Ship Weight (lbs)
	Cooling ¹	Gas Heating ²	CFM					W"	D"	H"		
DP5UM3008041A*	30,000	80,000	950	14.6/ 11.2	208/230-1	22.0	35	47	51	34½	76	407
DP5UM3608041A*	36,000	80,000	1180	15.2/ 11.2	208/230-1	25.8	35	47	51	42½	78	500

¹ BTU/h ² BTU/h

The manufacturing entity reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.

COMFORTABLE LIMITED WARRANTY* PROTECTION



* Complete warranty details available from your local dealer/contractor or at www.daikincomfort.com. To receive the Lifetime Heat Exchanger Limited Warranty (good for as long as you own your home), 12-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. The duration of warranty coverage in Texas and Florida differs in some cases. Additional requirements for annual maintenance are required for the Unit Replacement Limited Warranty. Online registration and some of the additional requirements are not required in California or Québec.

DP3GM

Packaged Gas & Electric

Up to 13.4 SEER2

Standard Features

- » Heavy-duty stainless-steel heat exchanger
- » Energy-efficient compressor
- » All-aluminum evaporator coil
- » Flowrater expansion device on 2- to 4-ton units
- » TXV expansion device on 5-ton units
- » Multi-speed ECM blower motor
- » Redundant gas valve with easy conversion to propane
- » Power-assisted combustion
- » Direct spark ignition system includes a microprocessor-based control for the entire ignition sequence, all blower operation, and all safety circuits complete with self-diagnostics
- » Can not be installed in California's South Coast Air Quality Management District (SCAQMD) and San Joaquin Valley Air Pollution Control District (SJVAPCD).
- » All models comply with California Low NOx standards.
- » AHRI Certified; ETL Listed
- » Fully insulated heavy-gauge, zinc-coated steel cabinet with UV-resistant powder-paint finish
- » Horizontal or downflow application
- » Aluminum foil-facing internal insulation reinforced with fiberglass scrim
- » Compressor sound blanket
- » Convenient access panels
- » One roof curb fits all units
- » One foot print: two heights

The DP3GM gas/electric packaged air conditioner offers energy-efficient cooling and heating performance in one self-contained unit. It comes with factory-installed compressor sound blanket that provides great noise dampening. Heavy-duty stainless-steel heat exchanger, all-aluminum evaporator coil, and multi-speed ECM blower motor are just a few features that come stock with this 13.4 SEER2 gas / electric HVAC unit. The fully insulated heavy-gauge, zinc-coated steel cabinet with UV-resistant grey powder-paint finish makes this unit very attractive. Supports 2023 DOE Energy Efficiency Standards.



**20
23**
SEER2

- » Bottom, 2" high base rails for easier handling
- » One footprint; two heights
- » When properly anchored, meets the 2020 Florida Building Code unit integrity requirements for hurricane-type winds (Anchor bracket kits available.)

Model	Nominal Ratings			SEER2 / EER2	Voltage-Phase	MCA	MOP	Dimensions			DBs	Ship Weight (lbs)
	Cooling (BTU/h)	Heating (BTU/h)	CFM					W"	D"	H"		
DP3GM2404041	24,000	40,000	800	13.4 / 10.6	208/230-1	21.6	35	47	51	34½	78	435
DP3GM2406041	24,000	60,000	800	13.4 / 10.6	208/230-1	21.6	35	47	51	34½	78	439
DP3GM3004041	30,000	40,000	1,000	13.4 / 10.6	208/230-1	22.8	35	47	51	34½	78	438
DP3GM3006041	30,000	60,000	1,000	13.4 / 10.6	208/230-1	22.8	35	47	51	34½	78	442
DP3GM3604041	36,000	40,000	1,200	13.4 / 10.6	208/230-1	22.8	35	47	51	34½	78	470
DP3GM3606041	36,000	60,000	1,200	13.4 / 10.6	208/230-1	22.8	35	47	51	34½	78	475
DP3GM3608041	36,000	80,000	1,200	13.4 / 10.6	208/230-1	22.8	35	47	51	34½	78	480
DP3GM4206041	42,000	60,000	1,300	13.4 / 10.6	208/230-1	29.2	45	47	51	34½	78	515
DP3GM4208041	42,000	80,000	1,300	13.4 / 10.6	208/230-1	29.2	45	47	51	34½	78	520
DP3GM4806041	48,000	60,000	1,525	13.4 / 10.6	208/230-1	32.3	50	47	51	42½	79	540
DP3GM4808041	48,000	80,000	1,525	13.4 / 10.6	208/230-1	32.3	50	47	51	42½	79	545
DP3GM4810041	48,000	100,000	1,525	13.4 / 10.6	208/230-1	32.3	50	47	51	42½	79	550
DP3GM6108041	60,000	80,000	1,750	13.4 / 10.6	208/230-1	41.0	60	47	51	42½	78	555
DP3GM6110041	60,000	100,000	1,750	13.4 / 10.6	208/230-1	41.0	60	47	51	42½	78	560
DP3GM6112041	60,000	120,000	1,750	13.4 / 10.6	208/230-1	41.0	60	47	51	42½	78	565

The manufacturing entity reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.

DP3UM

Packaged Gas & Electric Ultra-Low NO_x

Up to 13.4 SEER2 / 81% AFUE

COMFORTABLE LIMITED WARRANTY* PROTECTION



* Complete warranty details available from your local dealer/contractor or at www.daikincomfort.com. To receive the Lifetime Heat Exchanger Limited Warranty (good for as long as you own your home), 12-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. The duration of warranty coverage in Texas and Florida differs in some cases. Additional requirements for annual maintenance are required for the Unit Replacement Limited Warranty. Online registration and some of the additional requirements are not required in California or Québec.

Standard Features

- » Heavy-duty stainless-steel heat exchanger
- » Energy-efficient scroll compressor
- » Multi-Speed ECM indoor blower motor
- » Single-stage gas valve
- » All-aluminum evaporator coil
- » Flowrater expansion device on 2- to 4-ton units
- » TXV expansion device on 5-ton units
- » Power-assisted combustion
- » Direct spark ignition system includes a microprocessor-based control for the entire ignition sequence, all blower operation, and all safety circuits complete with self-diagnostics
- » All Ultra-Low NO_x DP3UM models comply with the 14 ng/J emission limit specified in the South Coast Air Quality Management District (SCAQMD) Rule 1111 and San Joaquin Valley Air Pollution Control District (SJVAPCD) Rule 4905. Learn more at www.aqmd.gov and www.valleyair.org.
- » AHRI Certified
- » ETL Listed
- » Fully insulated heavy-gauge, zinc-coated steel cabinet with UV-resistant powder-paint finish
- » Horizontal or downflow application
- » Aluminum foil-facing internal insulation reinforced with fiberglass scrim
- » Compressor sound blanket
- » Convenient access panels
- » One roof curb fits all units
- » One foot print: two heights
- » Bottom, 2" high base rails for easier handling
- » One footprint; two heights
- » When properly anchored, meets the 2020 Florida Building Code unit integrity requirements for hurricane-type winds (Anchor bracket kits available.)

The DP3UM Ultra-Low NO_x gas/electric packaged air conditioner offers energy-efficient cooling and heating performance in one self-contained unit. It comes with a factory-installed compressor sound blanket that provides great noise dampening. Heavy-duty stainless-steel heat exchanger, all-aluminum evaporator coil, and multi-speed ECM blower motor are just a few features that come stock with this 13.4 SEER2 gas / electric HVAC unit. The fully insulated heavy-gauge, zinc-coated steel cabinet with UV-resistant grey powder-paint finish makes this unit very attractive. Supports 2023 DOE Energy Efficiency Standards.



**20
23**
SEER2

Model	Nominal Ratings			SEER2 / EER2	Voltage- Phase	MCA	MOP	Dimensions			Ship Weight (lbs)
	Cooling (BTU/h)	Heating (BTU/h)	CFM					W"	D"	H"	
DP3UM2404041	24,000	40,000	800	13.4 / 10.6	208/230-1	21.6	35	47	51	34½	435
DP3UM3006041	30,000	60,000	1,000	13.4 / 10.6	208/230-1	22.8	35	47	51	34½	442
DP3UM3606041	36,000	60,000	1,200	13.4 / 10.6	208/230-1	22.8	35	47	51	34½	520
DP3UM4208041	42,000	80,000	1,300	13.4 / 10.6	208/230-1	29.2	45	47	51	42½	545
DP3UM4808041	48,000	80,000	1,525	13.4 / 10.6	208/230-1	32.3	50	47	51	42½	555
DP3UM6108041	60,000	80,000	1,700	13.4 / 10.6	208/230-1	41	60	47	51	42½	555

The manufacturing entity reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.

COMFORTABLE LIMITED WARRANTY* PROTECTION



* Complete warranty details available from your local dealer/contractor or at www.daikincomfort.com. To receive the Lifetime Heat Exchanger Limited Warranty (good for as long as you own your home), 6-Year Unit Replacement Limited Warranty and 12-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. The duration of warranty coverage in Texas and Florida differs in some cases.

Additional requirements for annual maintenance are required for the Unit Replacement Limited Warranty. Online registration and some of the additional requirements are not required in California or Québec.

DP3DM

Packaged Dual-Fuel

13.4 SEER2 / 80% AFUE

Standard Features

- » Combines cooling with heat pump and gas heating for optimal year-long performance
- » High-efficiency scroll compressor
- » Heavy-duty stainless-steel tubular heat exchanger
- » Multi-Speed ECM indoor blower motor
- » All-aluminum evaporator coil
- » Copper tube / aluminum fin coil
- » Two-stage gas valve; natural gas with easy conversion to propane with accessory kit
- » Power-assisted combustion
- » Loss-of-charge protection
- » Direct spark ignition system with a microprocessor-based control for the entire ignition sequence
- » All blower operation and all safety circuits complete with self-diagnostics
- » Can not be installed in California's South Coast Air Quality Management District (SCAQMD) and San Joaquin Valley Air Pollution Control District (SJVAPCD).
- » All models comply with California Low NOx standards.
- » AHRI Certified; ETL Listed
- » Fully insulated heavy-gauge, zinc-coated steel cabinet with UV-resistant powder-paint finish
- » Compressor sound blanket
- » Louvered metal panel condenser coil protection
- » Aluminum foil-facing internal insulation reinforced with fiberglass scrim
- » Horizontal or downflow application
- » Convenient access panels
- » One roof curb fits all units
- » Bottom, 2" high base rails for easy handling
- » All models fit a standard-size pick-up truck
- » When properly anchored, meets the 2020 Florida Building Code unit integrity requirements for hurricane-type winds (Anchor bracket kits available.)

The Daikin Brand DP3DM High-Efficiency Packaged Dual-Fuel unit provides indoor comfort and energy-efficient cooling with heat pump and gas heating for optimal year-long performance in one self-contained unit. It comes with a factory-installed compressor sound blanket that provides great noise dampening. Heavy-duty stainless-steel heat exchanger, all-aluminum evaporator coil, and multi-speed ECM blower motor are just a few features that come stock with this 13.4 SEER2 Dual-Fuel HVAC unit. The fully insulated heavy-gauge, zinc-coated steel cabinet with UV-resistant grey powder-paint finish makes this unit very attractive. Supports 2023 DOE Energy Efficiency Standards.



**20
23**
SEER2

UNITARY PRODUCTS

Model	Nominal Capacities (BTU/h)			SEER2 / EER2	Voltage- Phase	MCA	MOP	Dimensions			DBs	Ship Weight (lbs)
	Cooling	Heating	Gas Heat					W"	D"	H"		
DP3DM2406041	24,000	24,000	60,000	13.4 / 10.6	208-230/ 1/ 61	20.8	30	47	51	34½	76	440
DP3DM3008041	30,000	30,000	80,000	13.4 / 10.6	208-230/ 1/ 61	22.7	35	47	51	34½	76	440
DP3DM3608041	36,000	36,000	80,000	13.4 / 10.6	208-230/ 1/ 61	25.1	40	47	51	34½	76	460
DP3DM4210041	42,000	42,000	100,000	13.4 / 10.6	208-230/ 1/ 61	29.2	45	47	51	42½	76	545
DP3DM4810041	48,000	48,000	100,000	13.4 / 10.6	208-230/ 1/ 61	31.7	50	47	51	42½	76	545

The manufacturing entity reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.